

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Ferrules, 1.0 mm², taped, sleeve length: 8 mm, with plastic collar, galvanically tin-plated, color: red, color range according to DIN 46228-4, CSA-certified

The illustration shows version Al 1,5

-8 in red

#### **Product Features**

- Available in the main color ranges up to 2.5 mm²
- The taped ferrules were developed specifically for the crimping machine CF 3000 -2,5
- Can be used to wire all terminal blocks, especially those of the CLIPLINE complete system



## **Key Commercial Data**

| Packing unit                         | 1 pc            |
|--------------------------------------|-----------------|
| Minimum order quantity               | 1000 pc         |
| GTIN                                 | 4 017918 094881 |
| Weight per Piece (excluding packing) | 0.1382 g        |
| Custom tariff number                 | 85369010        |
| Country of origin                    | Germany         |

### Technical data

#### **Dimensions**

| Length (b)                                   | 14 mm  |
|--|--------|
| Maximum stripping length                     | 11 mm  |
| Sleeve length                                | 8 mm   |
| Inner dimension of the insulating collar (d) | 3 mm   |
| Ferrule diameter                             | 1.5 mm |
| Insulating collar thickness                  | 0.3 mm |



# Technical data

Sleeve wall thickness

Max. permanent temperature

### **Dimensions**

| Ambient conditions     |        |
|------------------------|--------|
| Short-term temperature | 120 °C |

0.15 mm

105 °C

### General

| Color                                  | red                            |
|--|--------------------------------|
| Components                             | free from silicone and halogen |
| Flammability rating according to UL 94 | НВ                             |
| Material                               | E-CU                           |
| Coating                                | tin-plated (galvanic)          |

## Standards and Regulations

| Connection in acc. with standard       | CSA |
|--|-----|
| Flammability rating according to UL 94 | НВ  |

# Classifications

## eCl@ss

| eCl@ss 4.0 | 27060701 |
|------------|----------|
|            | 27000701 |
| eCl@ss 4.1 | 27060701 |
| eCl@ss 5.0 | 27400201 |
| eCl@ss 5.1 | 27400201 |
| eCl@ss 6.0 | 27400201 |
| eCl@ss 7.0 | 27400201 |
| eCl@ss 8.0 | 27400201 |

### **ETIM**

| ETIM 2.0 | EC000005 |
|----------|----------|
| ETIM 3.0 | EC000005 |
| ETIM 4.0 | EC000005 |
| ETIM 5.0 | EC000005 |

## UNSPSC

| UNSPSC 6.01   | 30212109 |
|---------------|----------|
| UNSPSC 7.0901 | 27121703 |
| UNSPSC 11     | 27121703 |
| UNSPSC 12.01  | 27121703 |




## Classifications

**UNSPSC** UNSPSC 13.2 27121703 Approvals Approvals Approvals CSA / CSAus / EAC / EAC / cCSAus Ex Approvals Approvals submitted Approval details CSA @ **CSAus** EAC EAC cCSAus

Drawings



### Dimensional drawing



Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 3201385