

HTS - DIE SET FOR HSS CONTACTS 10 - 16 mm²


Matrize mit Handzange TE P/N 1-1105850-8 verwenden
Use die set with hand tool TE P/N 1-1105850-8

Matrize im Karton mit Bedienungsanleitung 411-18505 verpackt
Die set packed in a cardboard with instruction sheet 411-18505

Matrize zur Verarbeitung von HSS Kontakten wie unten gezeigt
Die set for processing of HSS Contacts as shown below

Querschnittgröße Wire Size mm ²	Kontakt TE P/N Contact TE P/N
10	4-1105150-1 4-1105150-2 4-1105151-1 4-1105151-2
16	5-1105150-1 5-1105150-2 5-1105151-1 5-1105151-2

Schraube M3x20
TE P/N 1-519005-6
Screw M3x20
TE P/N 1-519005-6



Schraube M4x10
TE P/N 519151-9
Screw M4x10
TE P/N 519151-9

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHERS AND PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM THE DIRECTOR OF COMMERCIAL

FREIMASSTOLERANZEN NACH DIN 7168 (WERTE IN mm)						
1) ABWEICHEND VON DIN 7168 2) LÄNGE DES KÜRZEREN SCHENKELS						
NENNMASS	ÜBER	0.5	3	6	30	120
	BIS	3	6	30	120	400
BEREICH 1)	LÄNGEN	100	150	200	300	400
	ABMASSE	100	150	200	300	400
ABMASSE	LÄNGEN	100	150	200	300	400
	MASSE	100	150	200	300	400
RADIEN U. FASEN	MITTEL	± 0.1	± 0.1	± 0.2	± 0.3	± 0.5
	± 0.8	± 0.2	± 0.5	± 1	± 2	± 4
WINKELABMASSE 1) 2)	± 1°	± 1°	± 30°	± 20°	± 10°	± 5°
GENERAL TOLERANCES ACC. TO DIN 7168 (VALUES IN mm)						
1) DEVIATING FROM DIN 7168		2) LENGTH OF SHORT ANGLE SIDE				

FINISH		Gewicht / Weight in Kg	
-		0,061	
DIMENSIONS:	mm	CHK	MATERIAL
		24.09.2008 P. Demmer	HEAT TREAT -
TOLERANCES UNLESS OTHERWISE SPECIFIED: n. ISO 8015 n. ISO 2768 n. DIN 16901 -		24.09.2008 Ch. Witt	
mm		APVD	Tyco Electronics AMP GmbH 64625 Bensheim (Germany)
 0 PLC ±. 1 PLC ±. 2 PLC ±. 3 PLC ±. 4 PLC ±.		24.09.2008 Ch. Witt	 Tyco Electronics
ANGLES:		NAME	
SURFACE TEXTURE		HTS - DIE SET FOR HSS CONTACTS HTS - Matrize für HSS Kontakte	
SCALE	SIZE	DRAWING NO	REV
2:1	A3	C-2-1105652-8	1 OF 1 A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-1105652-8](#) [3-1579021-0](#)