## XZCPA1141L10

pre-wired connectors XZ - straight female - M12 - 4 pins - cable PVC 10m

Product availability: Non-Stock - Not normally stocked in distribution facility



### Main

Commercial Status	Commercialised
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Pre-wired connectors
Series name	Application
Electrical connection	Straight female connector M12, 4 pins
Collar material	Stainless steel 316L
Status LED	Without
Cable length	32.81 ft (10 m)

#### Complementary

Cable connector fixing	Screw-on
Cable outer diameter	0.21 in (5.3 mm)
Cable composition	4 x 0.34 mm²
Wire insulation material	PVC
[Ue] rated operational voltage	300 V DC 250 V AC
[In] rated current	4 A
Contact resistance	<= 5000 μOhm
Insulating resistance	>= 1 GΩ
Product weight	0.82 lb(US) (0.37 kg)

#### **Environment**

IP degree of protection	IP69 K
Ambient air temperature for operation	-13185 °F (-2585 °C) (static)
Ambient air temperature for storage	-31212 °F (-35100 °C)

#### Ordering and shipping details

Category	22483 - MACHINE CABLES
Discount Schedule	DS3
GTIN	003389119021463
Nbr. of units in pkg.	1
Package weight(Lbs)	0.92
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	PL

#### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0601 - Schneider Electric declaration of conformity

#### Contractual warranty

Contraction Warranty		
Period	18 months	

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCPA1141L10