


- TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADERS ARE HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
- PARTS PACKAGED IN TUBES.
- .000100-.000200 MATTE TIN-LEAD OVER .000050 NICKEL.
- .000100-.000200 BRIGHT TIN OVER .000050 NICKEL.
- PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.
- HOUSING MATERIAL: FLAME RETARDANT THERMOPLASTIC; COLOR-BLACK.
- OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



REV	DESCRIPTION	DATE	DWN	APVD					
8	OB	.484	.400	4	5	5-103327-4			
7	OB	3.584	3.500	35	36	5-103327-3			
6	OB	1.584	1.500	15	16	5-103327-2			
5	OB	.384	.300	3	4	5-103327-1			
4	OB	1.384	1.300	13	14	5-103327-0			
3	OB	3.984	3.900	39	40	4-103327-9			
2	OB	.984	.900	9	10	4-103327-8			
1	OB	.784	.700	7	8	4-103327-7			
		.584	.500	5	6	4-103327-6			
		.284	.200	2	3	4-103327-5			
		.184	.100	1	2	4-103327-4			
		.084	—	—	1	4-103327-3			
	SUPERSEDED BY 1-103327-2	1.184	1.100	11	12	4-103327-2			
	SUPERSEDED BY 1-103327-1	1.084	1.000	10	11	4-103327-1			
		3.984	3.900	39	40	4-103327-0			
	OB	3.884	3.800	38	39	3-103327-9			
	OB	3.784	3.700	37	38	3-103327-8			
	OB	3.684	3.600	36	37	3-103327-7			
		3.584	3.500	35	36	3-103327-6			
	OB	3.484	3.400	34	35	3-103327-5			
	OB	3.384	3.300	33	34	3-103327-4			
	OB	3.284	3.200	32	33	3-103327-3			
	OB	3.184	3.100	31	32	3-103327-2			
	OB	3.084	3.000	30	31	3-103327-1			
	OB	2.984	2.900	29	30	3-103327-0			
	OB	2.884	2.800	28	29	2-103327-9			
	OB	2.784	2.700	27	28	2-103327-8			
	OB	2.684	2.600	26	27	2-103327-7			
	OB	2.584	2.500	25	26	2-103327-6			
	OB	2.484	2.400	24	25	2-103327-5			
	OB	2.384	2.300	23	24	2-103327-4			
	OB	2.284	2.200	22	23	2-103327-3			
	OB	2.184	2.100	21	22	2-103327-2			
	OB	2.084	2.000	20	21	2-103327-1			
	OB	1.984	1.900	19	20	2-103327-0			
	OB	1.884	1.800	18	19	1-103327-9			
		1.784	1.700	17	18	1-103327-8			
	OB	1.684	1.600	16	17	1-103327-7			
		1.584	1.500	15	16	1-103327-6			
	OB	1.484	1.400	14	15	1-103327-5			
		1.384	1.300	13	14	1-103327-4			
	OB	1.284	1.200	12	13	1-103327-3			
	SUPERSEDED BY 6-146278-2	1.184	1.100	11	12	1-103327-2			
		1.084	1.000	10	11	1-103327-1			
		.984	.900	9	10	1-103327-0			
	SUPERSEDED BY 5-146278-9	.884	.800	8	9	103327-9			
		.784	.700	7	8	103327-8			
		.684	.600	6	7	103327-7			
		.584	.500	5	6	103327-6			
		.484	.400	4	5	103327-5			
		.384	.300	3	4	103327-4			
		.284	.200	2	3	103327-3			
		.184	.100	1	2	103327-2			
		.084	—	—	1	103327-1			
PLATING	C	B	B	A	A	NO OF POSN		PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES. TOLERANCES UNLESS OTHERWISE SPECIFIED:

0. PLC	± .005
1. PLC	± .005
2. PLC	± .005
3. PLC	± .005
4. PLC	± .005
ANGLES	± .005

MATERIAL: POST: COPPER ALLOY. FINISH: SEE TABLE.

APPROVED: J. MARTINELLI (10/15/92), JOHN KNITTLE (23NOV92), B. FLINCHBAUGH (23NOV92).

NAME: ASSEMBLY, HEADER, BREAKAWAY, MOD II, SINGLE ROW, .100 C/L, VERTICAL, WITH .025 SQUARE POSTS.

SIZE: A1. CAGE CODE: 00779. DRAWING NO: 103327. WEIGHT: —. RESTRICTED TO: —.

CUSTOMER DRAWING. SCALE: 4:1. SHEET: 1 OF 1. REV: T.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[103327-8](#)