



Miniature Incandescent Indicators

WITH LIGHT SHIELD LENS CAPS
FOR MOUNTING IN 11/16" CLEARANCE HOLE
FOR 2 TO 55V OPERATION

See lamp ratings
on page K.

Recognized under the component
program of Underwriters'
Laboratories Inc.

75W., 125V.



MATERIALS AND FINISHES

- **Mounting Bushing and Light Shield Cap:** Standard—brass, black nickel finish.
- **Mounting Nut:** Brass, white nickel finish.
- **Internal-tooth Lockwasher:** Phosphor bronze, white nickel finish.
- **Terminals:** Solder — brass, hot tinned with elongated slot. Screw—brass, white nickel finish.



156-0410-2900-201

PUSH-PULL CAPS


156 SERIES

BASE PART NUMBERS

solder terminal	screw terminal
 169-0412-11-201	 169-1312-11-201

CAP PART NUMBERS

COMPLETE ASSEMBLY PART NUMBERS



PUSH-PULL ACTION

156-2900-200
variable opening, 0" to 1/4" x 3/8"

156-0410-2900-201

156-1310-2900-201

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Dialight:

[169-1312-11-201](#)