

Sensor/actuator cable - SAC-3P-MINMS/ 2,0-400 - 1531743

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Sensor/actuator cable, 3-position, PVC, yellow, Plug straight 7/8"-16UNF, A-coded, on free cable end, cable length: 2 m

Your advantages

- ☑ Robust connectors in size 7/8"-16UNF
- High-performance: connectors and cables with a large conductor cross section for power supply



Key Commercial Data

Packing unit	1 pc
GTIN	4 046356 024884
GTIN	4046356024884

Technical data

Dimensions

Length of cable	2 m

Ambient conditions

Ambient temperature (operation)	-25 °C 80 °C (Plug / socket)
Degree of protection	IP65
	IP67
	IP68

General

Rated current at 40°C	10 A
Rated voltage	300 V
Number of positions	3
Insulation resistance	\geq 10 M Ω
Coding	A - standard



Sensor/actuator cable - SAC-3P-MINMS/ 2,0-400 - 1531743

Technical data

General

Status display	No
Protective circuit/component	unwired
Overvoltage category	П
Degree of pollution	2
Test voltage	2500 V
Insertion/withdrawal cycles	> 500

Material

Flammability rating according to UL 94	НВ
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PUR
Material of grip body	PUR
Material, knurls	Nickel-plated brass

Cable

Cable type	PVC yellow IEC color code
Conductor cross section	0.75 mm²
AWG signal line	18
Conductor structure signal line	41x 0.16 mm
Wire colors	brown, blue, black
External sheath, color	yellow
External cable diameter	5.80 mm
Outer sheath, material	PVC

Standards and Regulations

Flammability rating according to UL 94	НВ

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings




Sensor/actuator cable - SAC-3P-MINMS/ 2,0-400 - 1531743

Schematic diagram




Pin assignment, plug, 7/8"-16UNF, 3-pos., view of male side

Dimensional drawing



7/8"-16UNF plug, straight

Circuit diagram



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1531743