



**Product:** <u>8741</u> ☑

Electronic, 2 Pr #22 Sol TC, PVC Ins, PVC Jkt, CMG

# Request Sample

# **Product Description**

Electronic, 2 Pair 22AWG (Solid) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

### **Technical Specifications**

# **Product Overview**

Suitable Applications: telephone cables; low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); voice communications

# **Physical Characteristics (Overall)**

#### Conductor

AWG	Stranding	Material	No. of Pairs
22	Solid	TC - Tinned Copper	2
Conductor Count: 4			
Total N	Number of Pa	airs:	2

# Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.01 in

#### **Color Chart**

Number	Color	
1	Black & Red	
2	Black & White	

# Outer Shield Material



#### **Outer Jacket Material**

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.23 in	0.032 in

# **Electrical Characteristics**

## Conductor DCR

Nominal Conductor DCR 16.5 Ohm/1000ft

## Capacitance

Nom. Capacitance Conductor to Conductor 30 pF/ft

#### Current

Max. Recommended Current [A]
2.24 Amps per conductor @ 20°C

#### Voltage

UL Description	UL Voltage Rating		
CMG	300 V RMS		
UL AWM Style 2576	150 V RMS		

#### **Temperature Range**

UL Temp Rating:	80°C (UL AWM Style 2576)
Operating Temp Range:	-20°C To +80°C

#### **Mechanical Characteristics**

Bulk Cable Weight:	23 lbs/1000ft
Max Recommended Pulling Tension:	30 lbs
Min Bend Radius/Minor Axis:	2.5 in

#### **Standards**

NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
UL AWM Style:	UL Style 2576 (150 V 80°C)

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

#### Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 FT4 Loading
CSA Flammability:	FT4
UL voltage rating:	300 V RMS

# Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	88741 or 82741 (Stranded conductors)

# **Part Number**

#### Variants

Item #	Color	Putup Type	Length	UPC
8741 060U500	Chrome	UnReel	500 ft	612825214885
8741 0601000	Chrome	Reel	1,000 ft	612825214892
8741 060U1000	Chrome	UnReel	1,000 ft	612825214878
8741 0605000	Chrome	Reel	5,000 ft	612825214908

Footnote: C - CRATE REEL PUT-UP.

# History

Update and Revision: Revision Number: 0.295 Revision Date: 04-28-2020

# © 2020 Belden, Inc

## All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

8741 060U1000 8741 060U500 8741 0601000