


**SLD Series**




**Agency Approvals**

Agency	Agency File Number
	E230531

**Maximum Ratings and Thermal Characteristics (T<sub>A</sub>=25°C unless otherwise noted)**

Parameter	Symbol	Value	Unit
Peak Pulse Power Dissipation 10ms x 150ms Test Waveform	P <sub>PPM</sub>	2200	W
Peak Pulse Power Dissipation 10µs x 1000µs Test Waveform	P <sub>PPM</sub>	5000	W
Steady State Power Dissipation on Infinite Heat Sink at T <sub>A</sub> =75°C (Fig. 6)	P <sub>D</sub>	8.0	W
Peak Forward Surge Current, 8.3ms Single Half Sine Wave (Note 3)	I <sub>FSM</sub>	600	A
Maximum Instantaneous Forward Voltage at 100A for Unidirectional Only	V <sub>F</sub>	3.5	V
Operating Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55 to 175	°C
Typical Thermal Resistance Junction to Lead	R <sub>θJL</sub>	8.0	°C/W
Typical Thermal Resistance Junction to Ambient	R <sub>θJA</sub>	40	°C/W

**Functional Diagram**



**Description**

The AEC-Q101 qualified SLD Series is packaged in a highly reliable industry standard P600 axial leaded package and is designed to provide precision overvoltage protection for sensitive electronics.

**Features**


- High reliability application and automotive grade AEC-Q101 qualified with T<sub>J</sub> 175°C
- V<sub>BR</sub> @ T<sub>J</sub> = V<sub>BR</sub> @ 25°C x (1 + α T x (T<sub>J</sub> - 25)) (α T: Temperature Coefficient, typical value is 0.1%)
- Glass passivated chip junction in P600 package
- Meets ISO7637 and ISO16750 load dump test; 2200W peak pulse capability at 10µs x 150ms waveform, repetition rate (duty cycles): 0.01%
- Fast response time: typically less than 1.0ps from 0 Volts to V<sub>BR</sub> min
- Excellent clamping capability
- Typical failure mode is short from over-specified voltage or current
- Whisker test is conducted based on JEDEC JESD201A per its table 4a and 4c
- IEC-61000-4-2 ESD 30kV(Air), 30kV (Contact)
- ESD protection of data lines in accordance with IEC 61000-4-2
- EFT protection of data lines in accordance with IEC 61000-4-4
- Low incremental surge resistance
- High temperature to reflow soldering guaranteed: 260°C/10sec / 0.375" (9.5mm) lead length, 5 lbs., (2.3kg) tension
- UL Recognized case material meeting flammability rating V-0.
- Matte tin lead-free plated
- Halogen free and RoHS compliant
- Pb-free E3 means 2nd level interconnect is Pb-free and the terminal finish material is tin(Sn) (IPC/ JEDEC J-STD-609A.01)

**Applications**

Designed to protect sensitive electronics from:

- Inductive Load Switching
- Alternator Load Dump


### Electrical Characteristics ( $T_A=25^\circ\text{C}$ unless otherwise noted)

Part Number (Uni)	Part Number (Bi)	Breakdown Voltage $V_{BR}$ @ $I_T$ (V)		Test Current $I_T$ (mA)	Reverse Stand off Voltage $V_R$ (Volts)	Maximum Reverse Leakage @ $V_R$ $I_R$ ( $\mu\text{A}$ )	Maximum Peak Pulse Current $I_{PP}$ (A)	Maximum Clamping Voltage @ $I_{PP}$ $V_C$ (V)	Agency Approval 
		MIN	MAX						
SLD10U-017	SLD10-018	11.8	13.0	5.0	10	10	300.0	17.0	x
SLD11U-017	SLD11-018	12.2	13.5	5.0	11	10	280.2	18.2	x
SLD12U-017	SLD12-018	13.3	14.7	5.0	12	10	256.3	19.9	x
SLD13U-017	SLD13-018	14.4	15.9	5.0	13	10	237.2	21.5	x
SLD14U-017	SLD14-018	15.6	17.2	5.0	14	10	219.8	23.2	x
SLD15U-017	SLD15-018	16.7	18.5	5.0	15	10	209.0	24.4	x
SLD16U-017	SLD16-018	18.0	19.3	5.0	16	10	196.2	26.0	x
SLD17U-017	SLD17-018	18.9	20.9	5.0	17	10	184.8	27.6	x
SLD18U-017	SLD18-018	20.0	22.1	5.0	18	10	174.7	29.2	x
SLD20U-017	SLD20-018	22.2	24.5	5.0	20	10	157.4	32.4	x
SLD22U-017	SLD22-018	24.4	26.9	5.0	22	10	143.7	35.5	x
SLD24U-017	SLD24-018	26.7	29.5	5.0	24	10	131.1	38.9	x
SLD26U-017	SLD26-018	28.9	31.9	5.0	26	10	121.1	42.1	x
SLD28U-017	SLD28-018	31.1	34.4	5.0	28	10	112.3	45.4	x
SLD30U-017	SLD30-018	33.3	36.8	5.0	30	10	105.4	48.4	x
SLD33U-017	SLD33-018	36.7	40.6	5.0	33	10	95.7	53.3	x
SLD36U-017	SLD36-018	40.0	44.2	5.0	36	10	87.8	58.1	x
SLD40U-017	SLD40-018	44.4	49.1	5.0	40	10	79.1	64.5	x
SLD43U-017	SLD43-018	49.0	54.2	5.0	43	10	73.5	69.4	x
SLD45U-017	SLD45-018	50.0	55.3	5.0	45	10	70.2	72.7	x
SLD48U-017	SLD48-018	53.3	58.9	5.0	48	10	65.9	77.4	x
SLD51U-017	SLD51-018	56.7	62.7	5.0	51	10	61.9	82.4	x
SLD54U-017	SLD54-018	60.0	66.3	5.0	54	10	58.6	87.1	x
SLD58U-017	SLD58-018	64.4	71.2	5.0	58	10	54.5	93.6	x
SLD60U-017	SLD60-018	68.4	75.6	5.0	60	10	52.7	96.8	x

**Notes:**

- $V_{BR}$  measured after  $I_T$  applied for 300 $\mu\text{s}$ ,  $I_T$  = square wave pulse or equivalent.
- Surge current waveform per 10 $\mu\text{s}$  x 1000 $\mu\text{s}$  exponential wave and derated per Fig. 4.
- All terms and symbols are consistent with ANSI/IEEE C62.35



### Load Dump Test Wave Form



Note: LF use  $t_d=400\text{ms}$  for 12V system test;  $t_d=350\text{ms}$  for 24V system

Parameter	12V system	24V system
$U_s$	65V to 87V	123V to 174V
$R_i$	0.5 $\Omega$ to 4 $\Omega$	1 $\Omega$ to 8 $\Omega$
$t_d$	40 ms to 400 ms	100 ms to 350 ms
$t_r$	(10 $^{-0.5}$ )ms	


**I-V Curve Characteristics**




- $P_{PPM}$  Peak Pulse Power Dissipation** ( $I_{PP} \times V_C$ ) – Max power dissipation
- $V_R$  Stand-off Voltage** – Maximum voltage that can be applied to the TVS without operation
- $V_{BR}$  Breakdown Voltage** – Maximum voltage that flows through the TVS at a specified test current ( $I_T$ )
- $V_C$  Clamping Voltage** – Peak voltage measured across the TVS at a specified  $I_{ppm}$  (peak impulse current)
- $I_R$  Reverse Leakage Current** – Current measured at  $V_R$
- $V_F$  Forward Voltage Drop for Uni-directional**

**Ratings and Characteristic Curves** ( $T_A=25^\circ\text{C}$  unless otherwise noted)


**Figure 1 - TVS Transients Clamping Waveform**




**Figure 2 - Peak Pulse Power Rating Curve**




**Figure 3 - Peak Pulse Power Derating Curve**





**Figure 4 - Typical Junction Capacitance**



**Figure 5 - Maximum Non-Repetitive Peak Forward Surge Current**



**Figure 6 - SOA Chart**



**Soldering Parameters**

**Flow/Wave Soldering (Solder Dipping)**

<b>Peak Temperature :</b>	265°C
<b>Dipping Time :</b>	10 seconds
<b>Soldering :</b>	1 time


**Physical Specifications**

<b>Weight</b>	0.07oz., 2.1g
<b>Case</b>	P600 molded plastic body over passivated junction.
<b>Polarity</b>	Color band denotes cathode for unidirectional components
<b>Terminal</b>	Matte Tin axial leads, solderable per JESD22-B102.

**Environmental Specifications**


<b>High Temp. Storage</b>	JESD22-A103
<b>HTRB</b>	JESD22-A108
<b>Temperature Cycling</b>	JESD22-A104
<b>H3TRB</b>	JESD22-A101
<b>RSH</b>	JESD22-B106

**Dimensions**




Dimensions	Inches		Millimeters	
	Min	Max	Min	Max
<b>A</b>	1.000	-	25.40	-
<b>B</b>	0.340	0.360	8.60	9.10
<b>C</b>	0.048	0.054	1.22	1.36
<b>D</b>	0.340	0.360	8.60	9.10

**Part Numbering System**




**Part Marking System**



**Packing Options**

Part Number	Component Package	Quantity	Packaging Option	Packaging Specification
SLDxxXXX	P600	800	Tape & Reel	EIA STD RS-296
SLDxxXX-B	P600	100	BOX	Littelfuse Spec.

**Tape and Reel Specification**



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Littelfuse:

[SLD24-018](#) [SLD10U-017-B](#) [SLD16-18-B](#) [SLD16U-017-B](#) [SLD24-18-B](#) [SLD24U-017-B](#) [SLD16-018](#) [SLD10U-017](#)  
[SLD16U-017](#) [SLD24U-017](#) [SLD10-018](#) [SLD30-018-100](#) [SLD60U-017](#) [SLD40-018-B](#) [SLD15-018-B](#) [SLD11U-017-B](#)  
[SLD13U-017-B](#) [SLD33U-017-B](#) [SLD26U-017](#) [SLD26-018-B](#) [SLD18-018](#) [SLD10-018-B](#) [SLD15U-017](#) [SLD17U-017-B](#)  
[SLD43U-017](#) [SLD30-018](#) [SLD28U-017-B](#) [SLD20-018-B](#) [SLD13-018-B](#) [SLD26-018](#) [SLD12-018](#) [SLD36U-017-B](#)  
[SLD28U-017](#) [SLD11-018-B](#) [SLD13-018](#) [SLD20-018](#) [SLD22-018-B](#) [SLD40U-017-B](#) [SLD15U-017-B](#) [SLD12-018-B](#)  
[SLD60-018](#) [SLD14-018](#) [SLD12U-017](#) [SLD30U-017-B](#) [SLD11U-017](#) [SLD18U-017-B](#) [SLD40-018](#) [SLD36U-017](#)  
[SLD17U-017](#) [SLD28-018](#) [SLD22U-017](#) [SLD36-018-B](#) [SLD14U-017-B](#) [SLD26U-017-B](#) [SLD11-018](#) [SLD18-018-B](#)  
[SLD18U-017](#) [SLD20U-017-B](#) [SLD36-018](#) [SLD13U-017](#) [SLD20U-017](#) [SLD22U-017-B](#) [SLD17-018-B](#) [SLD40U-017](#)  
[SLD28-018-B](#) [SLD17-018](#) [SLD14-018-B](#) [SLD22-018](#) [SLD30-018-B](#) [SLD33U-017](#) [SLD15-018](#) [SLD33-018-B](#) [SLD33-](#)  
[018](#) [SLD12U-017-B](#) [SLD43-018](#) [SLD30U-017](#) [SLD14U-017](#) [SLD43U-017-B](#) [SLD43-018-B](#) [SLD60-018-B](#) [SLD60U-](#)  
[017-B](#) [SLD16-018-B](#) [SLD24-018-B](#) [SLD45U-017](#) [SLD58-018-B](#) [SLD48U-017](#) [SLD51-018-B](#) [SLD54-018-B](#) [SLD54U-](#)  
[017](#) [SLD58-018](#) [SLD45-018](#) [SLD48-018-B](#) [SLD48U-017-B](#) [SLD58U-017-B](#) [SLD45U-017-B](#) [SLD45-018-B](#) [SLD48-](#)  
[018](#) [SLD51U-017](#) [SLD58U-017](#) [SLD54-018](#)