

Latching - UPR/ 2 - 3045567

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Latching, Number of positions: 2, Color: orange

Product Features

- Can be used in all plug versions
- Snapped into the outside of the plug housing and hooks onto the terminal block housing when the plug is snapped on



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
Weight per Piece (excluding packing)	1.24 g
Custom tariff number	85369010
Country of origin	Poland

Technical data

General

Color	orange
Material	PA-GF
Relative insulation material temperature index (Elec., UL 746 B)	65 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	115 °C

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145

Latching - UPR/ 2 - 3045567

Classifications

eCl@ss

eCl@ss 5.1	27141145
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27141190
eCl@ss 9.0	27141190

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002498
ETIM 5.0	EC002848

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121411
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

Approvals

Approvals

Approvals

EAC / EAC

Ex Approvals

Approvals submitted

Approval details

EAC

EAC

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[3045567](#)