

PIN RECEPTACLES

FOR 0,64 - 0,94 DIAMETER PINS AND 0,64 SQUARE PINS

<p>1305 1305-0-15-XX-47-XX-04-0 Press-fit in 1,55 mounting hole</p>	<p>1306 1306-0-15-XX-47-XX-04-0 Press-fit in 1,55 mounting hole</p>	<p>7305 7305-0-15-XX-47-XX-10-0 Solder mount in 1,52 min. mounting hole Also available on 8mm wide carrier tape: 6,000 parts per 330mm reel See page 194.9 for Tape & Reel details</p>	<p>0400 0400-0-15-XX-47-XX-04-0 Press-fit in 1,7 mounting hole</p>
<p>0335 0335-0-15-XX-47-XX-04-0 Hex press-fit in 1,63 plated through-hole</p>	<p>4614 4614-0-31-XX-47-XX-04-0 Compliant press-fit in 1,02 ± 0,08 plated hole. For 1,52 → 2,54 thick board</p>	<p>4615 4615-0-31-XX-47-XX-04-0 Compliant press-fit in 1,02 ± 0,08 plated hole. For 2,29 → 3,30 thick board</p>	<p>7614 7614-0-31-XX-47-XX-04-0 Compliant press-fit in 1,02 ± 0,08 plated hole. For 1,52 → 2,54 thick board</p>
<p>8401 8401-0-15-XX-47-XX-04-0 Hex press-fit in 1,6 plated through-hole</p>	<p>2400 2400-0-15-XX-47-XX-04-0 Press-fit in 1,68 mounting hole</p>	<p>6857 6857-0-15-XX-47-XX-10-0 Press-fit in 1,55 mounting hole</p>	<p>9393 9393-0-15-XX-47-XX-10-0 Press-fit in 1,70 mounting hole</p>

SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard

Contact Material: Beryllium Copper Alloy 172, HT

Dimensions: Millimeters

Tolerances On: Lengths: ± 0,13

Diameters: ± 0,051

Angles: ± 2°



ORDER CODE: XXXX - X - XX - XX - 47 - XX - XX - 0

BASIC PART #

SPECIFY SHELL FINISH:

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 15 0,25µm GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 27 0,76µm GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#47 CONTACT (DATA ON PAGE 256)

(For alternate contact choices, see group D on page 248)



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Mill-Max:](#)

[9393-0-15-01-47-01-10-0](#) [6857-0-15-15-47-27-10-0](#)