

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
AI	00		A1	ECR-17-000677	18JAN17	LS	GS

HTV10 HAND TOOL, Tandem Spring

FRONT VIEW



BACK VIEW



Eigenschaften / Features

Der Crimpkopf verfügt über drei Crimpnester in denen unterschiedliche Leitungsquerschnitte verarbeitet werden können. Die Kontakte werden über den Kontaktpositionierer in die richtige Ausgangsposition positioniert.

Crimping head featured with three crimping nests to enable processing of different wire sizes. Terminals will be correct inserted by Locator.

Crimpnester / Crimp nests

Anz. Pos.	cross-sectional area SQ.MM	AWG
1	0.03 - 0.09	32 - 28
2	0.2 - 0.56	24 - 20
3	0.12 - 0.14	26

Abmessungen / Dimension

Länge/Length: 193 mm

Breite/Width: 64 mm

Tiefe/Depth: 22 mm

Anwendungsbereich / Application range

cross-sectional area mm²	Crimp Height mm	TERMINALS
0,03 - 0,09	0,53 +/-0,03	167042-1
0,2 - 0,56	0,77 +/-0,03	166722-1
0,12 - 0,14	0,72 +/-0,03	166722-1

Bedienungsanleitung / Operating instructions

411-18618 / TE PN 6-744017-4



THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION


ALL INTERNATIONAL RIGHTS RESERVED.

BY TYCO ELECTRONICS CORPORATION.

© COPYRIGHT

DIMENSIONS:		DWN	C. Witt	21OCT2009	MATERIAL		FINISH		
mm		CHK	G. Stegmayer	21OCT2009	<div>TE Connectivity</div>				
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	G. Stegmayer	21OCT2009					
		PRODUCT SPEC		NAME					
0 PLC ± -		APPLICATION SPEC		HTV10 HAND TOOL, TANDEM SPRING		RESTRICTED TO			
1 PLC ± -				HTV10 Handzange, Tandem Spring					
2 PLC ± -				SIZE	CAGE CODE	DRAWING NO			
3 PLC ± -									
4 PLC ± -				A4 00779 C-169481-2			—		
ANGLES ± -									
		WEIGHT		0.27kg					
CUSTOMER DRAWING					SCALE		SHEET	1 OF 1	REV
									A1

0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ± -
ANGLES ± -



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[169481-2](#)