

Interface module - FLKM 14/8P/HF/PLC - 2295680

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

VARIOFACE termination board, for 8 channels, each with an additional terminal block per signal, for a common plus potential, halogen-free



Key Commercial Data

Packing unit	1 pc
GTIN	4 017918 429638
GTIN	4017918429638

Technical data

Dimensions

Width	56.3 mm
Height	77 mm

Ambient conditions

A b' t t t / t' \	1 00 00 00 00
Ambient temperature (operation)	1-20 °C 60 °C
Ambient temperature (operation)	1-20 O 00 O

General

Max. perm. operating voltage	60 V AC/DC	
Max. perm. current (per branch)	1 A	
Max. permissible current (all branches)	3 A (for plus and minus)	
Mounting position	any	
Degree of protection	IP00	

Connection data for connection 1

Connection name	Control side
Connection in acc. with standard	IEC 60603-13
Connection method	FLK14 pin strip
Number of positions	14

Connection data for connection 2

Connection name	Field level
Connection method	Screw connection
Conductor cross section solid	0.2 mm² 4 mm²
Conductor cross section flexible	0.2 mm² 2.5 mm²
Conductor cross section AWG	24 12



Interface module - FLKM 14/8P/HF/PLC - 2295680

Technical data

Connection data for connection 2

Number of positions	20

Standards and Regulations

Designation	Air clearances and creepage distances	
Standards/regulations	DIN EN 50178: 1998-04	
Rated insulation voltage	63 V	
Rated surge voltage	0.6 kV (1.2/50 μs)	
Insulation	Functional insulation	
Degree of pollution	2	
Overvoltage category	П	

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1	
China RoHS	Environmentally Friendly Use Period = 50	
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"	

Approvals

Αŗ	pr	O۷	als
----	----	----	-----

Approvals

EAC

Ex Approvals

Approval details

EAC [H[

RU C-DE.A*30.B.01742

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Fax +49 5235 3 41200

http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 2295680