



Product: <u>83304E</u> ☑

Electronic, 1 C #24 Str SPC, TFE Ins, OA SPC Brd, TFE Tape Jkt, MIL-W-16878/4 (Type E)

😭 Request Sample

Product Description

High Temperature Electronic, 1 Conductor 24AWG (19x36) Silver Plated Copper, TFE Insulation, Overall Silver Plated Copper Braid(85%) Shield, TFE Tape Outer Jacket, MIL-W-16878/4 (Type E)

Technical Specifications

Product Overview

| | MIL-W-1 | 78/4 (Type E) Spec; extreme high/low temperature environments; up to | 600V analog signals ; up to 600V voltage control |
|---|---|--|--|
| Physical Characteri | stics (Overall) | | |
| Conductor | | | |
| AWG Stranding | Material No. of Co | | |
| 24 19x36 SC - S | ilvered Copper 1 | | |
| Conductor Count: | 1 | | |
| nsulation | | | |
| Material | Material Trade Nam | Nominal Wall Thickness | |
| PTFE - Polytetrafluoroethy | lene Teflon® | 0.01 in | |
| | | | |
| White Duter Shield Material Type Material Braid SC - Silvered Copp Duter Jacket Material | Coverage [%] er 85 % | | |
| Outer Shield Material Type Material Braid SC - Silvered Copped | | Nominal Diameter Nominal Wall Thickness | |
| Duter Shield Material Type Material Braid SC - Silvered Copp | er 85 % Material Trade Nam | Nominal Diameter Nominal Wall Thickness 0.085 in 0.01 in | |
| Duter Shield Material Type Material Braid SC - Silvered Copp Duter Jacket Material Material | er 85 % Material Trade Nam ene Teflon® | | |
| Outer Shield Material Type Material Braid SC - Silvered Copp Outer Jacket Material Material PTFE - Polytetrafluoroethy | er 85 % Material Trade Nam ene Teflon® | | |
| Material Type Material Braid SC - Silvered Copp Duter Jacket Material Material Duter Jacket Material Material PTFE - Polytetrafluoroethy Electrical Character | er 85 % Material Trade Nam lene Teflon® | 0.085 in 0.01 in | |

Capacitance

Nom. Capacitance Conductor to Shield 46 pF/ft

Current

Max. Recommended Current [A] 4 Amps per conductor @ 25°C 600 V RMS

Temperature Range

| Operating Temp Range: | -65°C To +200°C |
|-----------------------|-----------------|
| | |

Mechanical Characteristics

| Bulk Cable Weight: | 8 lbs/1000ft |
|----------------------------------|--------------|
| Max Recommended Pulling Tension: | 15.5 lbs |
| Min Bend Radius/Minor Axis: | 1 in |

Standards

| Military Specification: | MIL-W-16878/4 (Type E except stranding), (insulated conductors) |
|-------------------------|---|
| Other Specification: | NEMA HP3 |

Applicable Environmental and Other Programs

| EU Directive 2000/53/EC (ELV): | Yes |
|---------------------------------------|-------------------------------|
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-01-01 |
| MII Order #39 (China RoHS): | Yes |

Flammability, LS0H, Toxicity Testing

| UL voltage rating: | 600 V RMS |
|--------------------|-----------|
| Plenum/Non-Plenum | |
| Plenum (Y/N): | No |

Part Number

Variants

roduct Note

| Notes: | Teflon« is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc. |
|----------------------|---|
| History | |
| Update and Revision: | Revision Number: 0.307 Revision Date: 04-28-2020 |

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

 Belden Wire & Cable:

 83304E 0091000
 83304E 009500