


SECTION B - B




10.82	5.84	55.32	13.56	15.37	11.20	61.11	52.81	66.93	PLUG	50	5	MDP308G - 50P2 - 001	1-1236089-0
10.82	5.84	57.71	10.72	12.55	8.36	63.50	55.42	69.32	PLUG	37	4	MDP308G - 37P2 - 001	1236089-9
10.82	5.84	41.30	10.72	12.55	8.36	47.04	38.96	53.04	PLUG	25	3	MDP308G - 25P2 - 001	1236089-8
10.72	5.97	27.51	10.72	12.55	8.36	33.32	25.25	39.14	PLUG	15	2	MDP308G - 15P2 - 001	1236089-7
10.72	5.97	19.28	10.72	12.55	8.36	24.99	16.92	30.81	PLUG	9	1	MDP308G - 9P2 - 001	1236089-6
10.82	5.84	55.32	13.56	15.37	11.20	61.11	52.81	66.93	PLUG WITH #20 PIN CONTACTS	50	5	MDP308G - 50P2	1236089-5
10.82	5.84	57.71	10.72	12.55	8.36	63.50	55.42	69.32	PLUG WITH #20 PIN CONTACTS	37	4	MDP308G - 37P2	1236089-4
10.82	5.84	41.30	10.72	12.55	8.36	47.04	38.96	53.04	PLUG WITH #20 PIN CONTACTS	25	3	MDP308G - 25P2	1236089-3
10.72	5.97	27.51	10.72	12.55	8.36	33.32	25.25	39.14	PLUG WITH #20 PIN CONTACTS	15	2	MDP308G - 15P2	1236089-2
10.72	5.97	19.28	10.72	12.55	8.36	24.99	16.92	30.81	PLUG WITH #20 PIN CONTACTS	9	1	MDP308G - 9P2	1236089-1
M±0.25	K±0.13	G±0.25	H±0.25	E±0.38	D±0.13	C±0.13	B±0.13	A±0.38	DESCRIPTION	Nb POS.	SIZE	OLD P/N	P/N 
												STANDARD MOUNT	

THIS DRAWING IS A CONTROLLED DOCUMENT.

	-

TOLERANCES UNLESS
OTHERWISE SPECIFIED:



ANGLES	±0.50
FINISH	NOTE 4

	-

TE Connectivity

SUB D PLUG
WITH WIRE BUSHING
MDP TYPE

9 C-1236089



—

6	REV F
---	-------

LOC		DIST		REVISIONS					
F		00		P	LTR	DESCRIPTION	DATE	DWN	APVD
					-	SEE SHEET 1	-	-	-

PLUG TYPE MDP

SECTION B - B



10.82	5.84	58.47	15.14	16.97	12.78	63.50	56.18	69.32	PLUG	104	6	MDP308G - 66104P2 - 001	4-1236089-1
10.82	5.84	55.32	13.56	15.37	11.20	61.11	52.81	66.93	PLUG	78	5	MDP308G - 5078P2 - 001	4-1236089-0
10.82	5.84	57.71	10.72	12.55	8.36	63.50	55.42	69.32	PLUG	62	4	MDP308G - 3762P2 - 001	3-1236089-9
10.82	5.84	41.30	10.72	12.55	8.36	47.04	38.96	53.04	PLUG	44	3	MDP308G - 2544P2 - 001	3-1236089-8
10.72	5.97	27.51	10.72	12.55	8.36	33.32	25.25	39.14	PLUG	26	2	MDP308G - 1526P2 - 001	3-1236089-7
10.72	5.97	19.28	10.72	12.55	8.36	24.99	16.92	30.81	PLUG	15	1	MDP308G - 915P2 - 001	3-1236089-6
10.82	5.84	58.47	15.14	16.97	12.78	63.50	56.18	69.32	PLUG WITH #22 PIN CONTACTS	104	6	MDP308G - 66104P2	3-1236089-5
10.82	5.84	55.32	13.56	15.37	11.20	61.11	52.81	66.93	PLUG WITH #22 PIN CONTACTS	78	5	MDP308G - 5078P2	3-1236089-4
10.82	5.84	57.71	10.72	12.55	8.36	63.50	55.42	69.32	PLUG WITH #22 PIN CONTACTS	62	4	MDP308G - 3762P2	3-1236089-3
10.82	5.84	41.30	10.72	12.55	8.36	47.04	38.96	53.04	PLUG WITH #22 PIN CONTACTS	44	3	MDP308G - 2544P2	3-1236089-2
10.72	5.97	27.51	10.72	12.55	8.36	33.32	25.25	39.14	PLUG WITH #22 PIN CONTACTS	26	2	MDP308G - 1526P2	3-1236089-1
10.72	5.97	19.28	10.72	12.55	8.36	24.99	16.92	30.81	PLUG WITH #22 PIN CONTACTS	15	1	MDP308G - 915P2	3-1236089-0
M±0.25	K±0.13	G±0.25	H±0.25	E±0.38	D±0.13	C±0.13	B±0.13	A±0.38	DESCRIPTION	NB POS	SIZE	OLD P/N	P/N 2
												STANDARD MOUNT HIGH DENSITE	

SEE NOTES ON LAST SHEET

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

MATERIAL
NOTE 3

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±0.5
1 PLC ±0.1
2 PLC ±0.02
3 PLC ±0.005
4 PLC ±0.005
ANGLES ±0.30°
FINISH NOTE 4

DWN J. THUEZ 29MAY2009
CHK Y. PETRONIN 03JUN2009
APVD Y. PETRONIN 03JUN2009
PRODUCT SPEC
APPLICATION SPEC NOTE 7
WEIGHT -

TE Connectivity

SUB D PLUG
WITH WIRE BUSHING
MDP TYPE

SIZE A3
CAGE CODE 00779
DRAWING NO C-1236089

RESTRICTED TO -


CUSTOMER DRAWING

SCALE 2:1


SHEET 2 OF 6

REV E

PLUG TYPE MDP



COUPE A - A
ECHELLE 4:1



10.82	5.84	55.32	13.56	15.37	11.20	61.11	52.81	66.93	PLUG	50	5	MDP308GF - 50P2 - 001	2-1236089-0
10.82	5.84	57.71	10.72	12.55	8.36	63.50	55.42	69.32	PLUG	37	4	MDP308GF - 37P2 - 001	1-1236089-9
10.82	5.84	41.30	10.72	12.55	8.36	47.04	38.96	53.04	PLUG	25	3	MDP308GF - 25P2 - 001	1-1236089-8
10.72	5.97	27.51	10.72	12.55	8.36	33.32	25.25	39.14	PLUG	15	2	MDP308GF - 15P2 - 001	1-1236089-7
10.72	5.97	19.28	10.72	12.55	8.36	24.99	16.92	30.81	PLUG	9	1	MDP308GF - 9P2 - 001	1-1236089-6
10.82	5.84	55.32	13.56	15.37	11.20	61.11	52.81	66.93	PLUG WITH #20 PIN CONTACTS	50	5	MDP308GF - 50P2	1-1236089-5
10.82	5.84	57.71	10.72	12.55	8.36	63.50	55.42	69.32	PLUG WITH #20 PIN CONTACTS	37	4	MDP308GF - 37P2	1-1236089-4
10.82	5.84	41.30	10.72	12.55	8.36	47.04	38.96	53.04	PLUG WITH #20 PIN CONTACTS	25	3	MDP308GF - 25P2	1-1236089-3
10.72	5.97	27.51	10.72	12.55	8.36	33.32	25.25	39.14	PLUG WITH #20 PIN CONTACTS	15	2	MDP308GF - 15P2	1-1236089-2
10.72	5.97	19.28	10.72	12.55	8.36	24.99	16.92	30.81	PLUG WITH #20 PIN CONTACTS	9	1	MDP308GF - 9P2	1-1236089-1
M±0.25	K±0.13	G±0.25	H±0.25	E±0.38	D±0.13	C±0.13	B±0.13	A±0.38	DESCRIPTION	Nb POS	SIZE	OLD P/N	P/N 2
												FLOATING BUSHING	

SEE NOTES ON LAST SHEET

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

MATERIAL
NOTE 3

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±0.5

1 PLC ±0.1

2 PLC ±0.02

3 PLC ±0.005

4 PLC ±0.005

ANGLES ±0.30°

FINISH

NOTE 4

DWN
J. THUEZ
CHK
Y. PETRONIN
APVD
Y. PETRONIN
PRODUCT SPEC
APPLICATION SPEC
NOTE 7
WEIGHT
-
CUSTOMER DRAWING

29MAY2009

03JUN2009

03JUN2009

1

NOTE 7

-

NAME
SUB D PLUG
WITH WIRE BUSHING
MDP TYPE

SIZE
A3

CAGE CODE
00779

DRAWING NO
C-1236089

RESTRICTED TO
-

SCALE
2:1


SHEET
3 OF 6

REV
E

TE Connectivity

TE

1470-19 (3/11)



4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

Tyco Electronics AMP GmbH

ALL RIGHTS RESERVED.

LOC

F

DIST

00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

MATING FACE OF PLUG SHOWN

CONFIGURATIONS FOR #20 CONTACTS

9 POSITION MS18273-1
SHELL SIZE 1

15 POSITION MS18274-1
SHELL SIZE 2

25 POSITION MS18275-1
SHELL SIZE 3

37 POSITION MS18276-1
SHELL SIZE 4

50 POSITION MS18277-1
SHELL SIZE 5

CONFIGURATIONS FOR #22 CONTACTS

MATING FACE OF PLUG SHOWN

15 POSITION MS18273-2
SHELL SIZE 1

26 POSITION MS18274-2
SHELL SIZE 2

44 POSITION MS18275-2
SHELL SIZE 3

62 POSITION MS18276-2
SHELL SIZE 4

78 POSITION MS18277-2
SHELL SIZE 5

104 POSITION MS14004-1
SHELL SIZE 6

SEE NOTES ON LAST SHEET

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±0.5
1 PLC	±0.1
2 PLC	±0.02
3 PLC	±0.005
4 PLC	±
ANGLES	±0.30°
FINISH	NOTE 4

MATERIAL

NOTE 3

DWN

J. THUEZ

29MAY2009

CHK

Y. PETRONIN

03JUN2009

APVD

Y. PETRONIN

03JUN2009

PRODUCT SPEC

-

APPLICATION SPEC

NOTE 7

WEIGHT

-

CUSTOMER DRAWING

TE Connectivity

NAME

SUB D PLUG
WITH WIRE BUSHING
MDP TYPE

SIZE

A3

CAGE CODE

00779

DRAWING NO

C-1236089

RESTRICTED TO

-

SCALE

2:1

SHEET

5

OF

6

REV

E

4

3

2

1

THIS DRAWING IS UNPUBLISHED.	RELEASED FOR PUBLICATION	20
© COPYRIGHT 20	Tyco Electronics AMP GmbH	ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	APVD
F	00		-	SEE SHEET I	-	-

1 THIS CONNECTOR MEETS THE REQUIREMENTS OF MIL-DTL-24308

2 PART NUMBER FOR ORDERING

3- MATERIALS :
SHELL : STEEL,CD PLATED
HOUSING : PBT,GLASS FILLED,UL94VO
RETAINING CLIP : STAINLESS STEEL
GROMMET : FLUOROSILICONE ELASTOMER
CONTACT:COPPER ALLOY,GOLD PLATED OVER NICKEL

4- CABLES EXTERNAL DIAMETER FOR CONTACTS #20 : Ø0.85 to Ø1.83
CABLES EXTERNAL DIAMETER FOR CONTACTS #22 : Ø1.37 MAX

5- CONNECTOR MARKING:
. MANUFACTURER IDENTIFICATION
. PART NUMBER
. DATE-CODE

6- INSERT ARRANGEMENT PER MIL-DTL-24308


7- FOR CONTACT CRIMPING INSTRUCTION SHEET REFER TO SPEC IS 7516
FOR CONTACT INSTALATION/ REMOVAL INSTRUCTION SHEET REFER TO SPEC IS 7508

8- #20 SOCKET CRIMP CONTACT P/N: 205090-1
#20 PIN CRIMP CONTACT P/N: 205089-1

#22D SOCKET CRIMP CONTACT P/N: 204351-1
#22D PIN CRIMP CONTACT P/N: 204370-2

9- INSERTION/EXTRACTION TOOL P/N: 91067-2
INSERTION/EXTRACTION TOOL P/N: 91067-1

10- CRIMP WITH HAND TOOL: 601966-1+ DIE INSERT : 601966-4
CRIMP WITH HAND TOOL: M22520/02-01 + POSITIONNER : M22520/02-06

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J. THUEZ	29MAY2009	 TE Connectivity		
		CHK Y. PETRONIN	03JUN2009			
DIMENSIONS: mm		APVD Y. PETRONIN	03JUN2009	NAME SUB D PLUG WITH WIRE BUSHING MDP TYPE		
		PRODUCT SPEC -				
		APPLICATION SPEC NOTE 7		SIZE A3	CAGE CODE 00779	DRAWING NO C-1236089
MATERIAL NOTE 3		FINISH NOTE 4	WEIGHT -	RESTRICTED TO -		
		CUSTOMER DRAWING		SCALE 2:1	SHEET 6 OF 6	REV E

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[3-1236089-9](#)