

-							
RCE	CKAGE: RCE INCH TORQUE = 8.3 POUND-FORCE ON METER TORQUE = 36.92NEWTON)						
	CE INCH TORQUE = II.I POUND-FORCE N METER TORQUE = 49.38NEWTON)						
REMOVAL TOOL P/N: 1542616-1.							
ND CERTIFIED.							
S,	5/8"	THRD.	7 F I	NS	2.000	.940	
S,	5/8"	THRD.	5 F I	NS	2.000	.740	
S,	5/8"	THRD.	4 F I	NS	2.000	.640	
S,	5/8"	THRD.	3 F I	NS	2.000	. 540	
S,	5/8"	THRD.	2 F I	NS	2.000	. 440	
S,	5/8"	THRD,	7 F I	NS	1.375	.940	
S,	5/8"	THRD,	5 F I	NS	Ι.375	.740	
S,	5/8"	THRD,	4 F I	NS	Ι.375	. 640	
S,	5/8"	THRD,	3 F I	NS	Ι.375	. 540	
S,	5/8"	THRD.	2 F I	NS	Ι.375	. 440	
DESCRIPTION					Ø <b>"B</b> "	DIM "A"	
TABLE 2							
0	CONFIDENTIAL PROPERTY OF TYCO TITLE: ELECTRONICS. NOT TO BE DISCLOSED TO OTHERS, REPRODUCED OR USED FOR ANY DIRDECEF EVENTS A STATUTION OF THE ASSEMBLY						
	ANY PURPOSES EXCEPT AS AUTHORIZED IN WRITING BY AN AUTHORIZED OFFICIAL OF TYCO ELECTRONICS. MUST BE RETURNED TO TYCO ELECTRONICS ON DEMAND						
	TO TYCO ELECTRONICS ON DEMAND, ON COMPLETION OF ORDER OR OTHER PURPOSES FOR WHICH LENT.						
	DIMENSIONS ARE IN: SCALE: INCHES 2:1			TE PART NO.: SHEET SEE TABLE 2 1011			
	THIRD ANGLE O + B			dwg. no.: rev. C-1963551 B			

```
SCREW DRIVER SLOT (.070 WIDE X .100 DEEP)PROVIDED
IN THE CENTER PORTION OF THE HEAT SINK. FOR ACCURATE
TORQUE SETTING, SCREW DRIVER BIT MUST BE ALIGNED
TO THE CENTER LINE OF THE HEAT SINK.
HEATSINK TORQUE SPECIFICATIONS CONVERTED TO FORCE.
       I.5 POUND-FORCE INCH TORQUE = 8.5 POUND-FORCE
          (0, 17 \text{ NEWTON METER TORQUE} = 37.81 \text{ NEWTON})
       2.0 POUND-FORCE INCH TORQUE = II.4 POUND-FORCE
```

BEFORE THE HEATSINK APPLICATION, THE USER SHOULD IDENTIFY THE SPECIFICATION OF MAXIMUM

BLACK PEI (UL94-VO)

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: <u>1-1963551-5</u>