

СS

A MAK

--- 5:25

<u>₩</u>

8|5

SΔ

92 b

KAMZIZ

4 -28UNF-2A 9 STUDS

+ 010 -.218 - 005 DIA HOLE 4 MTG HOLES

(2)

(6)

625 - MIN.

HOTES: I. MECH. INTERLOCK PREVENTS SIMULTANEOUS CLOSING OF BOTH SETS OF CONTACTS.

2. CONTACTOR DESIGNED TO THE BASIC REQUIREMENTS OF MIL-R-6106F UNLESS OTHERWISE SPECIFIED.

XAM 00.P-

XAM 87,5

6		CONNECTOR - M. 4 - 4 - 4 - 14 - 14 - 14 - 14 - 14 - 1	52514-016	- │
	MASHER 1/4 SPLIT BRONZE LOCK	ONZE LOCK	51807-034 (MS35338-101)	6
6	WASHER - FLAT 1/2 X 17/64 X .031 BR	17/64 X .031 BR.	51703-064 (AN9608416L)	80
6	NUT 1/4 -28 X 7/16 X 3/16 HEX BRASS	X 3/16 HEX BRASS	50407-364(MS35650-3255S	7
-	TERMINAL - SHIELD ASSEMBLY	SEMBLY	31164-10	9
-	CONTACTOR ASSEMBLY - PRIMARY	PRIMARY	34883- 30	N
-	PLATE - SCHEMATIC DIAGRAM	AGRAM	32163-1	7
-	PLATE - NAME		16043-1	r
_	PLATE - WARNING		17959-1	2
-	PLATE - WARNING	i	12771-1	1
ΦTY		NTURE OR		ITEM
EOD	DESCR	IPTION	DENTIFYING NO	Š
		PARTS LIST		
DATE	DATE 2-8-72 DR BY H.A.S.	HARTMAN FLF	HARTMAN ELECTRICAL MANUFACTURING	9
DESIG	DESIGNED FOR	DIV OF A-T-0	OHO LISEVEN	
	TOLERANCES			,
	THERWISE	CONTACT	CONTACTOR, ELECTRICAL	
00. 100.			TOOK DIGHTS	
	MATERIAL	I CO AMP, SIDE	I O AMP, SIDE SIABLE - SIDI.	
		115/2007	115/200 VAC, 400 HZ	
APPR	l	SECTION NO.		
	N N	_	B-349	
APPR				ł
	7	MCALE NONE WEIGHT		

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: