


REV. 0  
DCO 143671

COIL: @ 25°C	
RESISTANCE	1560 OHMS ± 10%
NOMINAL VOLTAGE	26.5 VDC
MUST OPERATE	14.2 VDC
MUST RELEASE	8.0 VDC MAX., 1.37 VDC MIN.

ENVIRONMENT:	
VIBRATION	10 Hz TO 3000 Hz @ 30 g's
SHOCK	75 g's 6 MS. DURATION
TEMPERATURE	-65 °C TO +125 °C
NOTES: OPERATE TIME 2.0 MS MAX.	
RELEASE TIME 1.5 MS MAX.	
CONTACT STABILIZATION 2.0 MS MAX.	

CUSTOMER DATA SHEET



TERMINAL VIEW

CONTACT RATING: LOW LEVEL TO 1A  
28 VDC RESISTIVE 100,000 OPERATIONS

DR. B.D. 14OCT02 CK *David C. 1/14/02*

**CII Technologies**  
advanced control electronic solutions

CUST. QPL  
CUST. NO. M39016/9-024M REV.

"JMA" RELAY

JMAP-26XM

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JMAP-26XM](#)