




Bestückungsplan / contact layout

■ bestückt / assembled

32 31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1



Leiterplatten-Lochbild / PCB drillhole pattern



Elastische Einpresszone / compliant pressfit zone

Isolierwerkstoff / housing material : PBT GF30

Bauart 7 / type 7

Anforderungsstufe 2 = 400 Steckzyklen / performance class 2 = 400 mating cycles

Fehlende Masse und Angaben nach IEC 60 603-2 / DIN EN 60 603-2

Missing information and dimensions per IEC 60 603-2 / DIN EN 60 603-2

Schichtaufbau im metallisierten Loch siehe Zeichnung 164062/Nr.6

diameter of drilled hole see drawing 164062/Nr.6

1)  $\varnothing 1,0 \pm 0.06$  Durchmesser des metallisierten Loches

$\varnothing 1,0 \pm 0.06$  Diameter of finished plated-through hole

$\varnothing 1,15 \pm 0.025$  Bohrungsdurchmesser des Loches

$\varnothing 1,15 \pm 0.025$  Diameter of drilled hole

Information:	Tolerances	Scale
All rights reserved. Only for information. To insure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		
Subject to modification without prior notice. Drawing will not be updated.		
b	23.02.2007	Designation
Index	Date	Federleiste C 96 EE Fem. Connector C 96 Pressfit
		224408
		STVC
		1
		H-00065895.SZA

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ERNI Electronics:](#)

[224408](#)