



FEATURES:

- Provides a quick and easy means of shorting two inputs of a miniature double banana jack.
- The plug to plug and jack to jack dimension is .500" (12,70mm) which is typical for double miniature banana plugs/jacks.
- ABS body provides insulation protection to the user.
- Shorting adapter has double miniature jacks at the topside for stacking capability.

MATERIALS:

Miniature Double Banana Jack (Top Side)

Body: Brass, Gold Plated

Insulation: ABS molded to banana plug and jack bodies

Marking: "POMONA ELECTRONICS CALIF.", "2035", "SHORTING BAR"

Miniature Double Banana Plug (Bottom Side)

Spring: Beryllium Copper, Gold Plated

Body: Brass, Nickel Plated

RATINGS:

Operating Voltage: 2500 VDC

Operating Temperature: +50°C (+122°F) Max.

Current: 5 Amperes

ORDERING INFORMATION: Model 2035-*

* = Standard colors, -0 Black, -2 Red

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Pomona:](#)

[2035-2](#) [2035-0](#)