







REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
F1		REVISED PER ECO-16-011475	11AUG2016	NK	JO

- 1

VOID CORING PERMISSIBLE IN POLARIZATION BAR.
- 2

EJECTOR FEATURES AT MOLDER'S DISCRETION (QUANTITY AND LOCATION).



1.798	17	36	1-104483-4
2.498	24	50	1-104483-3
.598	5	12	1-104483-2
.498	4	10	1-104483-1
2.598	25	52	1-104483-0
.698	6	14	104483-9
3.198	31	64	104483-8
2.698	26	54	104483-7
1.898	18	38	104483-6
1.498	14	30	104483-5
1.298	12	26	104483-4
.998	9	20	104483-3
.898	8	18	104483-2
.398	3	8	104483-1
A	NO OF SP	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN SCOTT A. SHUEY 17MAY99	TE Connectivity	
DIMENSIONS: INCHES		CHK H. MOLL 18MAY99	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD R. FLICKER 18MAY99	PRODUCT SPEC	
0 PLC ± -		APPLICATION SPEC		SIZE
1 PLC ± -		WEIGHT		CAGE CODE
2 PLC ± -		CUSTOMER DRAWING		DRAWING NO
3 PLC ± .005		SCALE 8:1		SHEET 1 OF 1
4 PLC ± -		REV F1		RESTRICTED TO
ANGLES ± -		A100779		104483
MATERIAL FLAME RETARDANT THERMOPLASTIC COLOR:BLACK		FINISH		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[104483-6](#)