


| REVISIONS | | | |
|-----------|--|----------|----------|
| LT# | DESCRIPTION | DATE | APPROVED |
| 1 | NC RELEASED TO DOCUMENT CONTROL PER DCR #SG87145 | 12/12/97 | GMR |



| ADAPTER, FRONT | | | |
|----------------|-----------------------------|---------|-------------------|
| SIZE | 'A' DIA +0.015 -0.000 | 'H' REF | V1 THREAD-MALE |
| A-SM | .312 | 1.84 | 7/8-12UNF-2A |
| A | .406 | 1.56 | 7/8-12UNF-2A |
| B | .515 | 1.56 | 1.0-12UNF-2A |
| C | .640 | 1.56 | 1 1/8-12UNF-2A |
| D | .750 | 1.91 | 1 1/4-12UNF-2A |
| E | .812 | 1.91 | 1 1/4-12UNF-2A |
| F | .843 | 1.91 | 1 5/16-12UNF-2A |
| G | .953 | 2.03 | 1 1/2-12UNF-2A |
| J | 1.062 | 2.03 | 1 5/8-12UNF-2A |
| K | 1.172 | 2.34 | 1 3/4-12UNF-2A |
| L | 1.265 | 2.34 | 1 13/16-12UNF-2A |
| M | 1.406 | 2.34 | 2-12UNF-2A |
| N | 1.515 | 2.34 | 2 1/16-12UNS-2A |
| P | 1.625 | 2.34 | 2 3/16-12UNS-2A |
| R | 1.750 | 2.58 | 2 5/16-12UNS-2A |
| S | 1.875 | 3.19 | 2 11/16-12UNS-2A |
| T | 2.062 | 3.19 | 2 7/8-12UNS-2A |
| V | 2.167 | 3.19 | 3.00-12UNS-2A |
| W | 2.312 | 3.19 | 3 1/8-12UNS-2A |

| FOLLOWER | | | |
|----------|-----------------------------|-----------------------------|---------|
| SIZE | 'A' DIA +0.015 -0.000 | 'E' DIA +0.005 -0.000 | 'L' REF |
| A-SM | .312 | .800 | .375 |
| A | .406 | .800 | .250 |
| B | .515 | .870 | .250 |
| C | .640 | .990 | .250 |
| D | .750 | 1.280 | .375 |
| E | .812 | 1.343 | .375 |
| F | .843 | 1.406 | .375 |
| G | .953 | 1.531 | .375 |
| J | 1.062 | 1.593 | .375 |
| K | 1.172 | 1.718 | .375 |
| L | 1.265 | 1.843 | .375 |
| M | 1.406 | 1.968 | .375 |
| N | 1.515 | 2.093 | .375 |
| P | 1.625 | 2.156 | .375 |
| R | 1.750 | 2.406 | .437 |
| S | 1.875 | 2.593 | .437 |
| T | 2.062 | 2.740 | .437 |
| V | 2.167 | 2.906 | .437 |
| W | 2.312 | 2.990 | .437 |

| REAR BODY | | | | |
|-----------|-----------------------------|---------|---------|---------|
| SIZE | 'A' DIA +0.015 -0.000 | 'C' DIA | 'R' REF | 'T' REF |
| A-SM | .312 | 1.100 | .550 | 1.64 |
| A | .406 | 1.100 | .550 | 1.40 |
| B | .515 | 1.100 | .550 | 1.40 |
| C | .640 | 1.100 | .550 | 1.40 |
| D | .750 | 1.512 | .796 | 1.89 |
| E | .812 | 1.512 | .796 | 1.89 |
| F | .843 | 1.512 | .796 | 1.89 |
| G | .953 | 1.512 | .796 | 1.89 |
| J | 1.062 | 1.512 | .796 | 1.89 |
| K | 1.172 | 2.210 | 1.093 | 2.20 |
| L | 1.265 | 2.210 | 1.093 | 2.20 |
| M | 1.406 | 2.210 | 1.093 | 2.20 |
| N | 1.515 | 2.210 | 1.093 | 2.20 |
| P | 1.625 | 3.572 | 1.625 | 2.72 |
| R | 1.750 | 3.572 | 1.625 | 2.78 |
| S | 1.875 | 3.572 | 1.625 | 2.78 |
| T | 2.062 | 3.572 | 1.625 | 2.78 |
| V | 2.167 | 3.572 | 1.625 | 2.78 |
| W | 2.312 | 3.572 | 1.625 | 2.78 |

| SPRINGS | | |
|-------------|------------|----------|
| SPRING SIZE | 'ID' ±.045 | 'OD' REF |
| A-SM | .312 | .780 |
| A | .437 | .780 |
| B | .546 | .890 |
| C | .656 | 1.000 |
| D | .761 | 1.310 |
| E | .843 | 1.375 |
| F | .875 | 1.405 |
| G | .984 | 1.515 |
| J | 1.093 | 1.625 |
| K | 1.203 | 1.735 |
| L | 1.297 | 1.830 |
| M | 1.437 | 1.970 |
| N | 1.546 | 2.075 |
| P | 1.655 | 2.185 |
| R | 1.781 | 2.440 |
| S | 1.906 | 2.565 |
| T | 2.093 | 2.755 |
| V | 2.218 | 2.880 |
| W | 2.343 | 3.000 |

NOTES:

- CABLE SHIELD GROUNDING ADAPTERS PROVIDE 360° GROUNDING TO OVERALL SHIELDED CABLES. THESE ARE FOR USED AT THE ENTRANCE TO STUFFING TUBES AND ARE AVAILABLE IN A VARIETY OF SIZES TO FIT VARIOUS THREADED ASSEMBLIES.

If this document is printed it becomes uncontrolled.
Check for the latest revision.

SPECIFICATION CONTROL DRAWING

| | | | |
|--|---|---|----------------------------|
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: DEC .XXX±.030 DEC .XX±.06 ANGLE ±2° MATERIAL FINISH | DATE 97Dec9 DESIGNED BY K.C.GAY DRAWN BY 97Dec18 THIRD ANGLE PROJECTION DWT NAME CSGASCDI PROJECT POL | DATE 97Dec9 TITLE CABLE SHIELD GROUNDING ADAPTER WITH MALE THREADS CODE IDENT. NO. D 06090 DWG. NO. CSGA-X SCALE NONE DO NOT SCALE THIS DRAWING | REV INC SHEET 1 OF 1 |
|--|---|---|----------------------------|

CSGA-X

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[CSGA-J](#)