



#### PERFORMANCE CHARACTERISTICS

1.5A AT 20°C (FULLY LOADED)

CURRENT RATING 1 A AT 70°C (FULLY LOADED)

RATED VOLTAGE : 500 V AC (CONT /CONT)

OPERATING TEMPERATURE : -55°C TO 125°C

CONTACT RESISTANCE 20 MO

INSERTION FORCE : 0.75N MAX/CONT.

EXTRACTION FORCE : 0.15N MIN/CONT

#### INSULATION RESISTANCE $\cdot 10^4$ MOHM

LEAD FREE INDICATOR :LF=LEAD FREE

2. THIS PRODUCT IS CSA APPROVED.  
THIS PRODUCT IS UL RECOGNIZED

THIS PRODUCT IS UL RECOGNIZED

3. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING :  
BS.A.201572.001

4. THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

 <a href="http://www.fciconnect.com">www.fciconnect.com</a>					tolerance 1DEC ±0.2 1DEC 2DEC ±0.1 2DEC ANGLES ±1° HOEKEN		MM 					
rev	ecn no	dr	date									
A	CONVERSION REVISION 01	KN	14-09-01	Dr	W.Panis	30-04-96	Product family	MILLIPICS	size	A4	Scale	3/1
B	DG05-0381	Kosor	10-10-05	Eng			Spec ref					
C	DG07-0362	Kosor	05-09-07	Chr			Material			ECN		
D	DG10-0110	NZ	03-22-10	Appr								
				Q	MPACS 8+2R RA RCP CONN TYPE F/NO SHIELDED				on	BS,C	,202258,003	
				+					gng			
				+								
					catalog no				CUMSTOMER		sheet 1 of 1	
					HM2R89PA8100----							

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[HM2R89PA8100N9LF](#)