


## CUSTOMER DRAWING



Product Name	Product Dimensions					Wire Dimensions			
	øA min	B nom	C nom	L max	Color (1)	Size Range mm² (AWG)	øG		
øG min	øG max								
B-106-3631	4.00 [0.160]	6.60 [0.260]	0.80 [0.030]	30.00 [1.180]	Red	0.5 - 1.0 (AWG 22-18)	1.4 [0.055]	4.0 [0.160]	
B-106-3632	4.60 [0.180]	6.60 [0.260]	0.80 [0.030]	32.00 [1.260]	Blue	1.5 - 2.5 (AWG 16-14)	2.0 [0.080]	4.6 [0.180]	
B-106-3633	6.50 [0.255]	6.60 [0.260]	0.80 [0.030]	33.00 [1.300]	Yellow	3.0 - 6.0 (AWG 12-10)	2.8 [0.110]	6.5 [0.255]	

### **MATERIALS**


1. INSULATION SLEEVE: Heat-shrinkable, transparent color (1), radiation cross-linked modified polyamide with thermoplastic adhesive coating inside.
2. PUSH-ON TERMINAL: Tin-plated brass.

BASE METAL: C260 (C26000) or C268 Brass.  
PLATING: Tin-plated per ASTM B545, Class A.

### **APPLICATION**

1. These controlled crimp devices are designed to terminate a tin-plated or bare copper stranded wire having an insulation rated for at least 75°C to a push-on terminal. It will provide a splash proof and strain relief connection.  
UL listed wire connector 3Z11.
2. Temperature range: -55°C to +125°C.
3. For application tooling and installation, see RPIP-684-00.

For best results, prepare the wire as shown:



			<b>TITLE:</b> <b>DURASEAL PUSH-ON RECEPTACLE</b>		
Unless otherwise specified dimensions are in millimeters. [Inches dimensions are shown in brackets]		Raychem Devices	DOCUMENT NO.:		
TOLERANCES: ANGLES: $\pm 0^{\circ}30'$		TE Connectivity reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application.	<b>B-106-3XXX</b>		
0.00 $\pm$ 0.02 MM 0.0 $\pm$ 0.2 MM 0 $\pm$ 0.5 MM	ROUGHNESS IN MICRON		REVISION:	D	DATE: FEB 22, 2017
PREPARED BY: YNGUYEN	CAGE CODE: 06090	REVISED PER: ECO-17-002136	SCALE:	NTS	SIZE: A SHEET: 1 of 1

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[B-106-3632CS100](#) [B-106-3631CS100](#)