

Universal Reversible USB 2.0 Cable (Reversible A to 5Pin Micro B M/M), 3 ft.

MODEL NUMBER: UR050-003



Universal / Reversible "A" connector allows plugging in any direction

Description

Tripp Lite UR050-003, 3ft USB 2.0 A to Micro-B cable, features a Universal / Reversible "A" connector, which takes the guesswork out of which way to position the "A" connector for plugging. Micro-USB is the next generation of USB connector that will be found on Cell Phones, PDA's, USB On-the-Go (OTG) devices, Digital Cameras, and more. Smaller and more durable (10,000 insertion cycles) than the existing mini-B connectors, the Micro-USB will also handle Power transfers, as well as Data. The USB Implementers Forum (USB-IF) has designed the Micro-USB to eliminate many of the proprietary Mini connectors found on different manufacturers digital devices, and it will be the standard USB connection on phones from the major cell phone manufacturers. USB 2.0 rated cable handles 480Mbps data transfer rates.

Features

- USB Universal / Reversible A Male to Micro-B Male
- Available in 3ft,6ft, and 10ft lengths
- 480Mbps USB 2.0 Data Transfer Rates
- Data and Power transference

Specifications

overview UPC Code 037332179555 INPUT

Highlights

- Next Generation USB Digital
 Device Connector
- Provides both Data and Power transfers
- USB 2.0 480Mbps Transfer rates
- Universal / Reversible "A" Male to Micro-B Male

System Requirements

 Digital devices that use the USB Micro-B Female socket

Package Includes

 3-ft. USB2.0 Universal / Reversible A to Micro-USB B Device Cable (A Male to Micro-B Male)



Cable Length (ft.) 3 Cable Length (m) 0.3 PHYSICAL Black Color Black Shipping Dimensions (httd / cm) 7.78 x 22.86 x 1.27 Shipping Dimensions (httd / in) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.05 Shipping Weight (kg) 0.11 Physical - Operating Temperature Range -104/75° C (14 to 167° F) Storage Temperature Range -104/75° C (14 to 167° F) Storage Temperature Range -104/80° C (-4 to 176° F) Storage Temperature Range -204/80° C (-4 to 176° F) Storage Temperature Range -REVERSIBLE USB A (MALE) Side A - Connector 1 MICRO-USB B (MALE) Storage SepECIFICATIONS		
PHYSICAL Color Black Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.05 Shipping Weight (bs.) 0.11 ENVIRONMENTAL 0.11 Operating Temperature Range -10/+75° C (14 to 167° F) Storage Temperature Range -20/+80° C (-4 to 176° F) CONNECTIONS Side A - Connector 1 Side B - Connector 1 REVERSIBLE USB A (MALE) Side B - Connector 1 MICRO-USB B (MALE) FEATURES & SPECIFICATIONS Technology VARRANTY Variantly Period	Cable Length (ft.)	3
Color Black Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.05 Shipping Weight (bs.) 0.11 ENVIRONMENTAL 0.0475° C (14 to 167° F) Storage Temperature Range -10/+75° C (14 to 167° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range MICRO-USB B (MALE) Storage Temperature Range MICRO-USB B (MALE) Technology USB 2.0 (High	Cable Length (m)	0.3
Color Black Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.05 Shipping Weight (bs.) 0.11 ENVIRONMENTAL 0.0475° C (14 to 167° F) Storage Temperature Range -10/+75° C (14 to 167° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range MICRO-USB B (MALE) Storage Temperature Range MICRO-USB B (MALE) Technology USB 2.0 (High		
Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.05 Shipping Weight (lbs.) 0.11 ENVIRONMENTAL Operating Temperature Range -10/+75° C (14 to 167° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Side A - Connector 1 REVERSIBLE USB A (MALE) Side B - Connector 1 MICRO-USB B (MALE) FEATURES & SPECIFICATIONS Technology USB 2.0 (High Speed); USB WARRANTY Product Warranty Period Listing limited warranty	PHYSICAL	
Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.05 Shipping Weight (lbs.) 0.11 ENVIRONMENTAL Operating Temperature Range -10/+75° C (14 to 167° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Storage Temperature Range -20/+80° C (-4 to 176° F) Side A - Connector 1 REVERSIBLE USB A (MALE) Side B - Connector 1 MICRO-USB B (MALE) FEATURES & SPECIFICATIONS Technology USB 2.0 (High Speed); USB WARRANTY Product Warranty Period Lifeting linging unsampler	Color	Black
Shipping Weight (kg) 0.05 Shipping Weight (bs.) 0.11 ENVIRONMENTAL Operating Temperature Range -10/+75° C (14 to 167° F) Storage Temperature Range -20/+80° C (-4 to 176° F) CONNECTIONS Side A - Connector 1 REVERSIBLE USB A (MALE) Side B - Connector 1 MICRO-USB B (MALE) FEATURES & SPECIFICATIONS Technology USB 2.0 (High Speed); USB WARRANTY Product Warranty Period Lifetime limited warranty	Shipping Dimensions (hwd / cm)	17.78 x 22.86 x 1.27
Shipping Weight (lbs.) 0.11 ENVIRONMENTAL Operating Temperature Range -10/+75° C (14 to 167° F) Storage Temperature Range -20/+80° C (-4 to 176° F) CONNECTIONS Side A - Connector 1 REVERSIBLE USB A (MALE) Side B - Connector 1 MICRO-USB B (MALE) FEATURES & SPECIFICATIONS Technology USB 2.0 (High Speed); USB WARRANTY Product Warranty Period Lifetime limited warranty	Shipping Dimensions (hwd / in.)	7.00 x 9.00 x 0.50
ENVIRONMENTAL Operating Temperature Range -10/+75° C (14 to 167° F) Storage Temperature Range -20/+80° C (-4 to 176° F) CONNECTIONS -20/+80° C (-4 to 176° F) Side A - Connector 1 REVERSIBLE USB A (MALE) Side B - Connector 1 MICRO-USB B (MALE) FEATURES & SPECIFICATIONS USB 2.0 (High Speed); USB WARRANTY Product Warranty Period	Shipping Weight (kg)	0.05
Operating Temperature Range -10/+75° C (14 to 167° F) Storage Temperature Range -20/+80° C (-4 to 176° F) CONNECTIONS Side A - Connector 1 REVERSIBLE USB A (MALE) Side B - Connector 1 MICRO-USB B (MALE) FEATURES & SPECIFICATIONS Technology USB 2.0 (High Speed); USB WARRANTY	Shipping Weight (lbs.)	0.11
Operating Temperature Range -10/+75° C (14 to 167° F) Storage Temperature Range -20/+80° C (-4 to 176° F) CONNECTIONS Side A - Connector 1 REVERSIBLE USB A (MALE) Side B - Connector 1 MICRO-USB B (MALE) FEATURES & SPECIFICATIONS Technology USB 2.0 (High Speed); USB WARRANTY		
Storage Temperature Range -20/+80° C (-4 to 176° F) CONNECTIONS Side A - Connector 1 REVERSIBLE USB A (MALE) Side B - Connector 1 MICRO-USB B (MALE) FEATURES & SPECIFICATIONS Technology USB 2.0 (High Speed); USB WARRANTY Product Warranty Period Lifetime limited warranty	ENVIRONMENTAL	
CONNECTIONS Side A - Connector 1 REVERSIBLE USB A (MALE) Side B - Connector 1 MICRO-USB B (MALE) FEATURES & SPECIFICATIONS Technology USB 2.0 (High Speed); USB WARRANTY Product Warranty Period Lifetime limited warranty	Operating Temperature Range	-10/+75° C (14 to 167° F)
Side A - Connector 1 REVERSIBLE USB A (MALE) Side B - Connector 1 MICRO-USB B (MALE) FEATURES & SPECIFICATIONS USB 2.0 (High Speed); USB Technology USB 2.0 (High Speed); USB WARRANTY Lifetime limited warranty	Storage Temperature Range	-20/+80° C (-4 to 176° F)
Side A - Connector 1 REVERSIBLE USB A (MALE) Side B - Connector 1 MICRO-USB B (MALE) FEATURES & SPECIFICATIONS USB 2.0 (High Speed); USB Technology USB 2.0 (High Speed); USB WARRANTY Lifetime limited warranty	CONNECTIONS	
Side B - Connector 1 MICRO-USB B (MALE) FEATURES & SPECIFICATIONS Technology USB 2.0 (High Speed); USB WARRANTY Volume Varianty Period	CONNECTIONS	
FEATURES & SPECIFICATIONS Technology USB 2.0 (High Speed); USB WARRANTY Product Warranty Period	Side A - Connector 1	REVERSIBLE USB A (MALE)
Technology USB 2.0 (High Speed); USB WARRANTY Product Warranty Period Lifetime limited warranty	Side B - Connector 1	MICRO-USB B (MALE)
Technology USB 2.0 (High Speed); USB WARRANTY Product Warranty Period Lifetime limited warranty	FEATURES & SPECIFICATIONS	
WARRANTY Product Warranty Period Lifetime limited warranty		LISE 2.0 (High Speed): LISE
Product Warranty Period		
Product Warranty Period (Worldwide) Lifetime limited warranty	WARRANTY	
	Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies