



| | | | | | |
|-------------------|-----|--|----------|-------|---------|
| 227-1221-X | | REVISIONS | | | |
| DRAWING NO. | REV | DESCRIPTION | DATE | ECO | APPR |
| THIRD ANGLE PROJ. | | RELEASE TO MFG. | 5/31/73 | 19829 | |
| | AA | REDRAWN WAS 'C' SIZE; ADD DASH -63 & NOTE 11 | 8/4/95 | 40734 | CPM/DR |
| | AB | ADD DASH -100 | 10/25/96 | 41606 | CPM/JJD |
| | AC | DASH 100, DIM 'A' WAS .263 | 4/5/00 | 43282 | CPM/ |
| | AD | DASH 25, Y110 SHOULD BE Y110P | 1/21/13 | 49408 | CPM/ |
| | AE | DASH 32, -61, -62, -63 ADD DANIELS PN | 11/5/13 | 49777 | CPM/ |

| STATUS | AMPHENOL PART No. | DANIELS PART No. | DIMENSIONS | | | | CABLE TYPE: RG-⟨⟩/U | CONNECTOR SERIES | |
|--------|-------------------|--------------------------|--|--|-----------|-----------|--|-----------------------------------|--|
| | | | ±.003 "A" | ±.003 "B" | ±.010 "C" | ±.010 "D" | | | |
| | 227-1221-09 | Y204P | .178 | .068 | .400 | .093 | 122, 180, 195, 21-597, 174, 179, 187, 188 | BNC, TNC-CAV. A&B, SMA-CAV. A | |
| | -11 | Y205P | .213 | .068 | .400 | .093 | 55, 58, 141, 142, 223, 303, 400 | BNC, TNC-CAV. A&B, UHF&SMA-CAV. A | |
| | -13 | Y206P | .255 | .068 | .400 | .093 | 59, 62, 140, 210 | BNC, TNC-CAV. A&B, UHF-CAV. A | |
| | -15 | Y207P | .263 | .068 | .400 | .093 | 71 | BNC, TNC-CAV. A & B | |
| | -25 | Y110P | .429 | .100 | .400 | .120 | 8, 9, 11, 87A, 149, 165, 213, 214, 216, 225, 393 | N-CAV. A&B | |
| | -29 | Y109P | .324 | .100 | .400 | .120 | 5, 6, 21, 143, 212, 222, 304 | N-CAV. A&B | |
| | -23 | Y145 | .384 | | .400 | | 8, 9, 11, 149, 213 | UHF | |
| | -57 | Y209P | .213 | .100 | .400 | .120 | 55, 58, 141, 142, 223, 303, 400 | N-CAV. A&B | |
| | -59 | Y208P | .255 | .100 | .400 | .120 | 59, 62, 140, 210 | N-CAV. A&B | |
| | -03 | Y196 | .128 | .105 | .325 | | 174, 179B, 186A, 187A, 316 | SMA | |
| □BS | -90 | | .312 ^{+.003} / _{-.002} | | .400 | | 3/16 DIA CABLE | SMA, TNC, N | |
| □BS | -35 | Y137 | .324 | .128 | .400 | .120 | SPECIAL NORTHRDP NA1-1253 | TNC, N | |
| □BS | -27 | Y151 | .532 | | .400 | | SPECIAL NORTHRDP NA1-1253 | TNC, N | |
| | -37 | Y138 | .314 | .151 | .400 | | GALILEO 3000-⟨X⟩S FIBER OPTIC | 905 & 906 SERIES | |
| □BS | -45 | Y143 | .231 | .218 | .400 | | VARIOUS FIBER OPTIC CABLE | 905 & 906 SERIES | |
| □BS | -39 | Y139 | .309 | .160 | .400 | | VARIOUS FIBER OPTIC CABLE | 905 & 906 SERIES | |
| □BS | -31 | Y150 | .501 | | .400 | | F/D STRAIN RELIEF | 801 MILTICHANNEL | |
| | -32 | Y369 | .324 | .068 | .400 | .093 | SPECIAL | | |
| □BS | -34 | | .263 | .100 | .400 | .120 | COMM-SCOPE F59SSV & 71 | N | |
| | -61 | Y1665 | .429 | .116 | .400 | .093 | BELDEN 9913 | REVERSE POLARITY TNC | |
| | -62 | Y1666 | .151 | .068 | .400 | .093 | SIMILAR TO RG178 | REVERSE POLARITY TNC | |
| | -63 | Y1710 | .429 | .116 ^{+.000} / _{-.003} | .400 | .120 | BELDEN 9913, 9914 | N | |
| □BS | -572 | | .300 | | .400 | | FOR 95-572-0500X SERIES ANTENNAS | | |
| □BS | 227-1221-2522 | SEE NOTE 5 | | | | | | | |
| □BS | 227-1221-1122 | SEE NOTE 6 (EAR 70853-0) | | | | | | | |
| □BS | 227-1221-100 | | .275 | .068 | .400 | .093 | 59 QUAD SHEILD & HEADEND | BNC | |

NOTES:

- DIES TO BE PACKAGED IN PLASTIC CONTAINERS SUPPLIED BY DANIELS MFG CORP. AMPHENOL PART No. MUST APPEAR ON TOP SIDE OF CONTAINER. SIZE: 1-1/4" L x 1-1/4" W x 1-1/4" H.
- MATERIAL: CRIMPING DIES - TOOL STEEL. HEAT TREAT TO ROCKWELL C52-60.
- FINISH: ON CRIMPING SURFACES 32 MICROINCHES MAX. BLACK OXIDE COATING PER MIL-C-13924.
- DIES SHALL BE SUPPLIED WITH APPROPRIATE ROLL PINS.
- SAME AS -25 EXCEPT PACKAGE PER AMPHENOL SPEC 349-50371, SHEET 2, WANG PART No. 723-0350.
- (SAME AS -11) PACKAGE DIE WITH PLASTIC CONTAINER IN UNPRINTED BAG 999-256. BAG SHALL BE STAMPED WITH DATE CODE AND WANG PART No. "723-0391-1022". FOR PACKAGING & SHIPPING PROCEDURE SEE SPEC 349-50371.
- MANUFACTURED BY DANIELS MFG CORP., BLOOMFIELD, MICHIGAN.
- USED IN CONJUNCT WITH AMPHENOL TOOL FRAME PART No. 227-944. (DANIELS MFG CORP. TOOL FRAME HX4).
- DIMENSIONS SHOWN ARE AT FULLY BUTTED CONDITIONS.
- BASIC DIE DIMENSIONS MUST BE PER MIL-C-22520/5C.
- DO NOT SCALE THIS DRAWING.

| | | | | | |
|---|---|---------------------------------------|------------------|---------------------------|--|
| UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL ±.015 (0,381 mm) ±.005 (0,127 mm) | MATERIAL MATERIAL SEE NOTE 2. QQ-B-628, CLASS B FINISH SEE NOTE 3. | DRAWN T. ALBERA | DATE 9/20/89 | TITLE HEX CRIMP DIE | Amphenol Amphenol Corporation RF/Microwave Operations Danbury, Conn. U.S.A. 06810 |
| | | ENGINEER D. ROYCE | DATE 9/29/89 | | |
| NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data. | REFERENCE | APPROVED D. ROYCE | DATE 9/29/89 | SCALE: 1:1 | SHEET OF |
| | | CAD FILE F:\DEPT611\TOOLS\227\1221 | CODE ID 74868 | DWG SIZE B | DRAWING NO. 227-1221-X |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[227-1221-9](#)