

STATSHIELD® STANDARD MOISTURE BARRIER BAG



Meets Requirements of: ESD Protective Packaging Level 2 Technical Requirements

ANSI/ESD STM11.31

Modified incline plane

Modified incline plane

IPC-TM-650 2.4.1

EIA 541

Typical Values Test Procedures/Method ANSI/ESD STM11.11

 1×10^4 to < 1 x 10¹¹ ohms <10 nJ 20 volts

-0.09 nC/sq. in. +0.10 nC/sq. in.

Nominal 0.0035" (.0889mm) ±10% MIL-STD-3010, 1003 Nominal -0" / + 0.125" Nominal ± 1/8" Offset 0 to 1/4" >20 lbs MIL-STD-3010, 2065 >11 (lb/in width) ASTM D1876-93 >12 PSI ASTM D882 **ASTM F1249** ≤0.02/g/100sq.in/24hours Not detected FTIR Pass MIL-STD-3010, M3005

ANSI/ESD S541 Section 6.2 Outside an EPA

"Transportation of sensitive products outside of an EPA shall require packaging that provides:

Pass

- 1. Low charge generation
- 2. Dissipative or conductive materials for intimate contact
- 3. A structure that provides electrostatic discharge shielding."

RoHS 2, REACH and Conflict Minerals Statement

None of the RoHS 2 restricted materials, REACH substances of very high concern as of 2016/06/20, or Conflict Minerals are intentionally added in manufacturing this product. Ref. European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE. See Desco Limited Warranty at Desco.com.

Statshield® and Statfree® are Registered Trademarks of Desco Industries Inc. See Bag Selection Chart Click HERE.

Made in the United States of America

Specifications and procedures subject to change without notice.

STATSHIELD® STANDARD, MOISTURE BARRIER BAG, 0.0035" (0.0889mm) DESCO DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com DRAWING DATE: PHONE (909) 627-8178 NUMBER August DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021 13806 2016 PHONE (781) 821-8370

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Desco:

13820 13810 13829 13816 13826 13828 13808 13824 13830 13832 13811 13822 13804 13812