


Coaxial PCB Connector 82_MMCX-S50-0-2/111_K

Description

Straight PCB jack

Interface Standards
SUHNER-MMCX



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 6 GHz

Mechanical Data

Board mounting type edge mount
Weight 0.0007 kg

Environmental Data

Operating temperature -55 °C to 155 °C
2011/65/EU (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (Nickel underplated)
Body	Brass	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	

Related Documents

Outline drawing DOU-00013081
Catalogue drawing DCA-00013083

Ordering Information

Bulk 100 pcs package 82_MMCX-S50-0-2/111_KH
Tape and Reel package 82_MMCX-S50-0-2/111_KG
Single package 82_MMCX-S50-0-2/111_KE

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[82_MMCX-S50-0-2/111_KE](#)