



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

UF4001GP THRU UF4007GP

Features

- Halogen free available upon request by adding suffix "-HF"
- Ultra Fast Switching Speed For High Efficiency
- Low Leakage
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Lead Free Finish/RoHS Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)

Maximum Ratings


- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Typical Thermal Resistance 40°C/W

MCC	Device	Maximum	Maximum	Maximum
Catalog	Marking	Recurrent	RMS	DC
Number		Peak Reverse	Voltage	Blocking
		Voltage	_	Voltage
UF4001GP	UF4001GP	50V	35V	50V
UF4002GP	UF4002GP	100V	70V	100V
UF4003GP	UF4003GP	200V	140V	200V
UF4004GP	UF4004GP	400V	280V	400V
UF4005GP	UF4005GP	600V	420V	400V
UF4006GP	UF4006GP	800V	560V	800V
UF4007GP	UF4007GP	1000V	700V	1000V

Electrical Characteristics @ 25°C Unless Otherwise Specified

iiooti ioai oiiai aotoi io		Oniooo o	uioi mioo opooiiiou
Average Forward Current	$I_{F(AV)}$	1 A	T _A = 55°C
Peak Forward Surge Current	I _{FSM}	30A	8.3ms, half sine
Maximum Instantaneous Forward Voltage			
UF4001GP-4003GP UF4004GP UF4005GP-4007GP	V_{F}	1.0 V 1.3 V 1.7 V	I _{FM} = 1.0A; T _A = 25°C
Maximum DC			
Reverse Current At Rated DC Blocking	I_R	5 uA 100uA	T _A = 25°C T _A = 100°C
Voltage		TOULA	T _A = 100 C
Maximum Reverse			
Recovery Time UF4001GP-4004GP	T_{rr}	50ns	I _F =0.5A, I _R =1.0A,
UF4005GP-4007GP		75ns	I _{rr} =0.25A
Typical Junction			
Capacitance			
UF4001GP-4004GP	\mathbf{C}_{J}	20pF	Measured at
UF4005GP-4007GP		10pF	1.0MHz, V _R =4.0V

DO-41



DIMENSIONS							
	INCHES		MM				
DIM	MIN	MAX	MIN	MAX	NOTE		
Α	.166	.205	4.10	5.20			
В	.080	.107	2.00	2.70			
O	.028	.034	.70	.90			
D	1.000		25.40				

Note: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

¹ Amp Glass
Passivated Ultra Fast
Recovery Rectifier
50 to 1000 Volts


^{*}Pulse Test: Pulse Width 300µsec, Duty Cycle 1%


UF4001GP thru UF4007GP




FIG.1 - FORWARD CURRENT DERATING CURVE 1.0 AVERAGE FORWARD CURRENT AMPERES 8.0 0.6 SINGLE PHASE HALF WAVE 60Hz RESISTIVE OR INDUCTIVE LOAD 0.1 L 25

AMBIENT TEMPERATURE, ℃







175

150



Ordering Information:

Device	Packing	
Part Number-TP	Tape&Reel: 5Kpcs/Reel	
Part Number-AP	Ammo Packing: 5Kpcs/Ammo Box	
Part Number-BP	Bulk: 50Kpcs/Carton	

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Micro Commercial Components (MCC): UF4004GP-TP UF4007GP-TP