

Harmony products

Main

| | |
|---------------------------------|--|
| Commercial Status | Commercialised |
| Range of product | Harmony XAC |
| Product or component type | Head for pushbutton |
| Component name | XACB |
| Marking | Unmarked |
| Operator additional information | Booted |
| Operating travel | 0.63 in (16 mm) |
| Cap/Operator or lens colour | Black |
| Product compatibility | XESD1181 XESD1191 XESD1281 XESD1291 |
| Sale per indivisible quantity | 10 |

Complementary

| | |
|----------------|------------------------|
| Product weight | 0.01 lb(US) (0.005 kg) |
|----------------|------------------------|

Environment

| | |
|--|---|
| Standards | EN 60947-5-1 IEC 60947-5-1 CSA C22.2 No 14 |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) |
| Vibration resistance | 15 gn (f = 10...500 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 100 gn conforming to IEC 60068-2-27 |
| Class of protection against electric shock | Class II |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to EN 50102 |

Ordering and shipping details

| | |
|-----------------------|---|
| Category | 22473 - PUSHBUTTON, PENDANTS |
| Discount Schedule | CS2 |
| GTIN | 00785901640943 |
| Nbr. of units in pkg. | 10 |
| Package weight(Lbs) | 0.01 |
| Product availability | Stock - Normally stocked in distribution facility |
| Returnability | Y |
| Country of origin | CZ |

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XACB9212](#)