

Adapter - HC-NPT-3/4-M25 - 1686850

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



NPT adapter, IP68, up to 5 bar, incl. O-ring seal, M25 to 3/4"

The illustration shows version HC-NPT-1/2-M20



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	59.528 g
Custom tariff number	74199990
Country of origin	Germany

Technical data

Dimensions

Length	28 mm
Length without connecting thread	21 mm
Connecting thread diameter	25 mm
Wrench size, union nut	30 mm
Hexagon angular dimension GRP	30 mm
Length of the connecting thread	7 mm

Ambient conditions

Degree of protection	IP68 (Depends on the screw connection used)
Ambient temperature (operation)	-20 °C ... 80 °C

General

Material	Nickel-plated brass
Cable gland material	Nickel-plated brass
O-ring material	NBR
Thread type on connection side	M25

Adapter - HC-NPT-3/4-M25 - 1686850

Technical data

General

Thread type on seal side	3/4 inch NPT
Color	silver

Classifications

eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	27149109
eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 7.0	27149109
eCl@ss 8.0	27439207

ETIM

ETIM 2.0	EC000441
ETIM 3.0	EC000441
ETIM 4.0	EC000441
ETIM 5.0	EC000938

UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

Approvals

Approvals

Approvals

EAC

Ex Approvals

Adapter - HC-NPT-3/4-M25 - 1686850

Approvals


Approvals submitted

Approval details


EAC

Drawings

Dimensional drawing



Dimensional drawing



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact:

1686850