


4805 (3/11)

ro/ENGINEER DRAWING

		2						1			
	LOC	DIST				REVISIO	NS				
	АD	00	Ρ	LTR		DESCRIPTIC	DN		DATE	DWN	APVD
		•		A2	REVISED PER	ECO-11-0048	335	11	MAR2011	RK	HMR
IAL: HIGH IAL: PHOS					THERMOPL	ASTIC,	color; [BLACK.			
H: NICKEL T PLI PEF EIA-7007	RFORM	ИА N С Е	E F	REQU	I I R E M E N T Ś	OF IND	USTRY	ĒS			
NS AND BA SULT AMP A PC BOA	ENG							THE			
APE ON RE	EELS	PER	ΕI	A - 4	81.						
TER HOLE ACUUM PLA						NG POST	STYLE	"A" AN	ID PL	AC I	NG
R LANDS M S OPTIMUN OF CONNEC	M SOL	_ D E R					HOWEVER	2.4			
S DIM H =	= 10.	3±0	.	ΙN	EIA 700A	AAB SPE	CIFICAT	ION.			
H: 0.0038 A, 0.0012 0127 MIN	27 M	ΙΝΙΜΙ	JМ	GOL	D PER AS	TM B 48	8 ON MA	TING A Entire	REA, Con	TAC	Τ.
AMOND SHA	APED	POST	ΤS								
POSTS											


D

В



ASTYLE B POSTS

FERIAL



•								
8	44.4	45.9	44.22	4	4 , 5	84	3-5120524-2	
	34.4	35.9	34.22	31	4 , 5	64	3-5 20524-	
2	44.4	45.9	45.9 44.22		4 , 5	84	2-5120524-2	
. /2	34.4	35.9	35.9 34.22		4 , 5	64	2-5120524-1	
8	44.4	45.9	44.22	4	4 , 5	84	-5 20524-2	
. /8	34.4	35.9	34.22	31	4 , 5	64	-5 20524-	
2	44.4	45.9	44.22	4	4, 5	84	5 20524 - 2	
/2	34.4	35.9	34.22	31	4 , 5	64	5 2 0 5 2 4 - 1	
NISH	DIM D	DIM C	DIM B	DIM A	STACK HGTS	POS	PART NO	
	LLED DOCUMEN	CHK D WED	<u>BO</u> 29S	ÉPO4 EPO4	<u>ڪ T</u> E	TE C	onnectivity	
TO OTH	DLERANCES UNLESS ERWISE SPECIFIE	D: APVD R.WER	295	EP04 name		_		
O PLC ±- 1 PLC ±- 2 PLC ±0.03 3 PLC ±0.003 Application spec RCPT ASSY, I.Omm FH(IEEEI386) CONNECTOR							EEEI386)	
4 PLC ANGLES	±-	- ' 4 -	25045	SIZE	CAGE CODE DRAWING NO		RESTRICTED TO	
FINISH	-	WEIGHT	-	A 1 0) 0 7 7 9 <mark>C = </mark> 5 2 (0524	-	
	SEE TABLE	CUSTOME	ER DRAWING	I	S	CALE 0 : SH	eet of RevA2	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: <u>1-5120524-2</u>