


CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



* DIMENSION MAY BE EXCEEDED WITH SOLDER ONLY



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	2-4 @20°C	0.031 ohms ±20%
D.C. RESISTANCE	8-7 @20°C	0.090 ohms ±20%
D.C. RESISTANCE	6-5 @20°C	0.070 ohms ±20%
INDUCTANCE	2-4 100kHz, 100mVAC, Ls	2.5uH ±10%
⑥ SATURATION CURRENT	20% Rolloff from initial	12A
LEAKAGE INDUCTANCE	2-4 tie(5+6+7+8), 100kHz, 10mVAC, Ls	125nH max.
DIELECTRIC	2-8 tie(6+7), 2500VAC, 1 second	2500VAC, 1 minute
DIELECTRIC	2-8 tie(6+7), 4000VDC, 1 second	-
URNS RATIO	(8-5):(2-4), tie(6+7)	2.5:1, ±1%
URNS RATIO	(8-7):(6-5)	1:1, ±1%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Safety Standard Undefined.

Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

DETAILS SUBJECT TO CHANGE

REV.	DATE	Packaging Specifications Method: Tape & Reel PKG-0410 www.we-online.com/midcom		Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64 Decimals: ±.005 [.13] Footprint: ±.005 [.13]	DRAWING TITLE TRANSFORMER	PART NO. 750311880
6C	7/18					
6B	8/13					
6A	2/11	SEE REVISION SHEET FOR REVISION LEVEL		This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eiSos p/n: 750311880	SPECIFICATION SHEET 1 OF 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Wurth Electronics:](#)

[750311880](#)