

RECOMMENDED MOUNTING HOLE



				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007” .315 – 1.180 = ± 0.015” 1.180 – 4.724 = ± 0.020” DO NOT SCALE DRAWING	APPROVALS		DATE		Amphenol Connex							
8						DRAWN	G.R.S.	07/28/06					PART DESCRIPTION SMB BULKHEAD CRIMP JACK (FOR RG-316U/D CABLE)			
7	HEAT SHRINK TUBE				1	CHECKED										
6	FERRULE	COPPER	NICKEL		1	ISSUED			PART NO. 142180							
5	HEX NUT	BRASS	NICKEL		1	SHEET	1 OF 1						DWG. NO. 142180.DWG REV. A SIZE A SCALE NA			
4	LOCK WASHER	BRASS	NICKEL		1											
3	CONTACT PIN	BRASS	GOLD		1											
2	INSULATOR	TEFLON	NATURAL		1											
1	BODY	BRASS	NICKEL	1												
DESCRIPTION		MATERIAL	FINISH	QTY	CAD FILE		C:/142/142180.DWG		DWG. NO. 142180.DWG		REV. A	SIZE A	SCALE NA			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[142180](#)