

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	REVISED PER ECO-14-009591	07OCT2014	NK	MM

DIM A

9.20±0.20

POLARIZATION KEY SLOT

2.41 REF

0.80±0.02

3.81±0.05

7.25

3.40±0.30

0.80±0.02

8.00±0.15

3.81

Ø 1.2^{+0.1}₀

Ø 0.1

RECOMMENDED PC BOARD LAYOUT

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±⁻

1 PLC ±0.3

2 PLC ±0.25

3 PLC ±⁻

4 PLC ±⁻

ANGLES ±2°

MATERIAL

1

FINISH

-

DWN

S. SCHLEGEL

06JAN2010

CHK

C. RICHARD

06JAN2010

APVD

C. RICHARD

06JAN2010

PRODUCT SPEC

-

APPLICATION SPEC

-

WEIGHT

-

CUSTOMER DRAWING

TE

TE Connectivity

NAME

TERMINAL BLOCK HEADER ASSEMBLY, 90 DEGREE, CLOSED ENDS, 3.81mm PITCH

SIZE

A3

CAGE CODE

00779

DRAWING NO

C-1776135

RESTRICTED TO

-

SCALE

4:1

SHEET

1

OF

1

REV

A

1 MATERIALS AND FINISH:
HOUSING: HIGH TEMPERATURE POLYAMIDE, UL94V-0
COLOR: BLACK.
TERMINAL: PHOSPHOR BRONZE, TIN PLATED.

2 SUITABLE FOR 1.6-2.4mm PC BOARD THICKNESS.

3 UL RATING: 300V, 11A.

46.73	12	1-1776135-2
42.92	11	1-1776135-1
39.11	10	1-1776135-0
35.30	9	1776135-9
31.49	8	1776135-8
27.68	7	1776135-7
23.87	6	1776135-6
20.06	5	1776135-5
16.25	4	1776135-4
12.44	3	1776135-3
8.63	2	1776135-2
DIM A	NO OF POS.	PART NUMBER

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1776135-5](#)