

## Bus system cable - SAC-4P-M12MSD/ 5,0-933/M12MSD - 1524381

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Bus system cable, PROFINET CAT5 (100 Mbps), 4-position, PVC/PVC, green RAL 6018, shielded, Plug straight M12, coding: D, on Plug straight M12, coding: D, cable length: 5 m



### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 1 pc                                                                                                    |
| GTIN         | <br>4 046356 021463 |
| GTIN         | 4046356021463                                                                                           |

### Technical data

#### Dimensions

|                 |     |
|-----------------|-----|
| Length of cable | 5 m |
|-----------------|-----|

#### Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket) |
| Degree of protection            | IP65                             |
|                                 | IP67                             |

#### General

|                       |                                                                                                                                                                                                |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Note                  | This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 10.1 Cord Sets for Balanced Cabling |
| Rated current at 40°C | 4 A                                                                                                                                                                                            |
| Rated voltage         | 48 V AC                                                                                                                                                                                        |
|                       | 60 V DC                                                                                                                                                                                        |
| Number of positions   | 4                                                                                                                                                                                              |
| Insulation resistance | ≥ 100 MΩ                                                                                                                                                                                       |
| Coding                | D - data                                                                                                                                                                                       |
| Status display        | No                                                                                                                                                                                             |
| Overvoltage category  | II                                                                                                                                                                                             |

# Bus system cable - SAC-4P-M12MSD/ 5,0-933/M12MSD - 1524381

## Technical data

### General

|                             |       |
|-----------------------------|-------|
| Degree of pollution         | 3     |
| Insertion/withdrawal cycles | ≥ 100 |

### Material

|                                        |                                             |
|----------------------------------------|---------------------------------------------|
| Flammability rating according to UL 94 | V0                                          |
| Contact material                       | CuSn                                        |
| Contact surface material               | Ni/Au                                       |
| Contact carrier material               | PA 6.6                                      |
| Material of grip body                  | TPU, hardly inflammable, self-extinguishing |
| Material, knurls                       | Zinc die-cast, nickel-plated                |
| Sealing material                       | NBR                                         |

### Standards and Regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V0 |
|----------------------------------------|----|

### Cable

|                                               |                                                    |
|-----------------------------------------------|----------------------------------------------------|
| Cable abbreviation                            | 2YY(ST)CY                                          |
| UL AWM style                                  | 21694                                              |
| Cable structure                               | 1x4xAWG22/7; SF/TQ                                 |
| Conductor cross section                       | 4x 0.34 mm <sup>2</sup>                            |
| AWG signal line                               | 22                                                 |
| Conductor structure signal line               | 7x 0.25 mm                                         |
| Core diameter including insulation            | 1.55 mm                                            |
| Wire colors                                   | White, yellow, blue, orange                        |
| Overall twist                                 | Star quad                                          |
| Shielding                                     | Aluminum-coated foil, tinned copper braided shield |
| Optical shield covering                       | 85 %                                               |
| External sheath, color                        | green RAL 6018                                     |
| Outer sheath thickness                        | approx. 0.9 mm                                     |
| External cable diameter D                     | 6.5 mm ±0.2 mm                                     |
| Minimum bending radius, fixed installation    | 3 x D                                              |
| Minimum bending radius, flexible installation | 7 x D                                              |
| Cable weight                                  | 67 kg/km                                           |
| Outer sheath, material                        | PVC                                                |
| Material, inner sheath                        | PVC                                                |
| Material conductor insulation                 | PE                                                 |
| Conductor material                            | Tin-plated Cu litz wires                           |
| Insulation resistance                         | ≥ 500 MΩ*km                                        |
| Loop resistance                               | ≤ 120.00 Ω/km                                      |
| Wave impedance                                | 100 Ω ±15 Ω (at 100 MHz)                           |
| Near end crosstalk attenuation (NEXT)         | 80 dB (with 1 MHz)                                 |
|                                               | 76 dB (at 4 MHz)                                   |

## Bus system cable - SAC-4P-M12MSD/ 5,0-933/M12MSD - 1524381

### Technical data

#### Cable

|                                 |                                                 |
|---------------------------------|-------------------------------------------------|
|                                 | 70 dB (at 10 MHz)                               |
|                                 | 65 dB (at 16 MHz)                               |
|                                 | 63 dB (at 20 MHz)                               |
|                                 | 60 dB (at 31.25 MHz)                            |
|                                 | 55 dB (at 62.5 MHz)                             |
|                                 | 50 dB (at 100 MHz)                              |
| Attenuation                     | 2.1 dB (with 1 MHz)                             |
|                                 | 4 dB (at 4 MHz)                                 |
|                                 | 6.3 dB (at 10 MHz)                              |
|                                 | 8 dB (at 16 MHz)                                |
|                                 | 9 dB (at 20 MHz)                                |
|                                 | 11.4 dB (at 31.25 MHz)                          |
|                                 | 16.5 dB (at 62.5 MHz)                           |
|                                 | 21.3 dB (at 100 MHz)                            |
| Signal speed                    | 0.66 c                                          |
| Signal runtime                  | 5.3 ns/m                                        |
| Coupling resistance             | ≤ 20.00 mΩ/m (at 10 MHz)                        |
| Nominal voltage, cable          | 600 V                                           |
| Test voltage Core/Core          | 2000 V (50 Hz, 1 min.)                          |
| Test voltage Core/Shield        | 2000 V (50 Hz, 1 min.)                          |
| Flame resistance                | according to UL 1685 (CSA FT 4)                 |
| Resistance to oil               | Resistant to oil to a limited extent            |
| Other resistance                | UV resistant According to UL 1581, Section 1200 |
| Ambient temperature (operation) | -40 °C ... 70 °C (cable, fixed installation)    |
|                                 | -40 °C ... 70 °C (cable, flexible installation) |


#### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

### Drawings


## Bus system cable - SAC-4P-M12MSD/ 5,0-933/M12MSD - 1524381

Dimensional drawing




Plug, M12 x 1, straight, shielded

Dimensional drawing




Plug, M12 x 1, straight, shielded

Circuit diagram



## Bus system cable - SAC-4P-M12MSD/ 5,0-933/M12MSD - 1524381


Schematic diagram



Pin assignment M12 male connector, 4-pos., D-coded, male side

## Bus system cable - SAC-4P-M12MSD/ 5,0-933/M12MSD - 1524381


Schematic diagram



Pin assignment M12 male connector, 4-pos., D-coded, male side

## Bus system cable - SAC-4P-M12MSD/ 5,0-933/M12MSD - 1524381

Cable cross section



PROFINET PVC stranded CAT5 [93B]

### Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060300 |
| eCl@ss 4.1 | 27060300 |
| eCl@ss 5.0 | 27061800 |
| eCl@ss 5.1 | 27061800 |
| eCl@ss 6.0 | 27279200 |
| eCl@ss 7.0 | 27279218 |
| eCl@ss 8.0 | 27279218 |
| eCl@ss 9.0 | 27060308 |

## Bus system cable - SAC-4P-M12MSD/ 5,0-933/M12MSD - 1524381

### Classifications

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000830 |
| ETIM 3.0 | EC001855 |
| ETIM 4.0 | EC001855 |
| ETIM 5.0 | EC002599 |
| ETIM 6.0 | EC001262 |
| ETIM 7.0 | EC001262 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31251501 |
| UNSPSC 7.0901 | 31251501 |
| UNSPSC 11     | 31251501 |
| UNSPSC 12.01  | 31251501 |
| UNSPSC 13.2   | 31251501 |
| UNSPSC 18.0   | 26121604 |
| UNSPSC 19.0   | 26121604 |
| UNSPSC 20.0   | 26121604 |
| UNSPSC 21.0   | 26121604 |

### Approvals

#### Approvals

#### Approvals

#### EAC

#### Ex Approvals

#### Approval details

|     |                                                                                     |                          |
|-----|-------------------------------------------------------------------------------------|--------------------------|
| EAC |  | RU C-<br>DE.BL08.B.00286 |
|-----|-------------------------------------------------------------------------------------|--------------------------|



Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>