

6 OPTIONAL WIRESHIELD P/N 7-1419157-8 (SOLD SEPARATELY). PLEASE CONTACT YOUR TE SALES REPRESENTATIVE FOR AVAILABILITY AND PRICING.



KEYING OPTION "A" SHOWN			
6	CPA	PBT 15% GF	RED
5	PERIMETER SEAL	SILICONE	GREEN
4	GROMMET	SILICONE	BROWN
3	COVER	PA66 35% GF	BLACK
2	TPA WITH 3 SHORTING BAR POSITIONS CONFIGURATION	sPS 30% GF	RED
1	PLUG WITH KEYING OPTION "F" AND 3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK
1	PLUG WITH KEYING OPTION "E" AND 3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK
1	PLUG WITH KEYING OPTION "D" AND 3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK
1	PLUG WITH KEYING OPTION "C" AND 3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	NATURAL
1	PLUG WITH KEYING OPTION "B" AND 3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK
1	PLUG WITH KEYING OPTION "A" AND 3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	GRAY
ITEM	DESCRIPTION	MATERIAL	FINISH/COLOR

4805 (3/11)

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWG M 16APR2002 CHK M FORISKA 16APR2002 REV'D A VALASKA 16APR2002	 TE Connectivity	
DIMENSIONS: mm		NAME 24 WAY ARM, PRODUCT SPEC PLUG ASSEMBLY WITHOUT SHORTING BARS, APPLICATION SPEC CUSTOMER SPEC.		
		SIZE CASE CODE DRAWING NO. RESTRICTED TO A1 00779 C=3-1419157-9		
MATERIAL - SEE CHART ABOVE		WEIGHT - CUSTOMER DRAWING SCALE 3:1 SHEET 2 OF 3 REV BM		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-1438356-5](#)