



Product availability: Non-Stock - Not normally stocked in distribution facility



### Main

|                               |  |
|-------------------------------|--|
| Commercial Status             | Commercialised   |
| Range of product              | OsiSense XC  |
| Series name                   | Standard compact   |
| Product or component type     | Limit switch body  |
| Device short name             | ZCD  |
| Design                        | Compact  |
| Body type                     | Fixed  |
| Associated head               | ZCE01<br>ZCE02<br>ZCE05<br>ZCE06<br>ZCE07<br>ZCE08<br>ZCE09<br>ZCE10<br>ZCE11<br>ZCE13<br>ZCE14<br>ZCE21<br>ZCE24<br>ZCE27<br>ZCE28<br>ZCE29<br>ZCE62<br>ZCE63<br>ZCE64<br>ZCE65<br>ZCE66<br>ZCE67<br>ZCEH0<br>ZCEH2 |
| Body material                 | Zamak  |
| Number of poles               | 2  |
| Contacts type and composition | 2 NC   |
| Contacts operation            | Snap action, simultaneous  |

### Complementary

|                                 |  |
|---------------------------------|--|
| Associated connection component | ZCDEF12<br>ZCDEG11<br>ZCDEG13<br>ZCDEN12<br>ZCDEP16<br>ZCDEP20   |
| Electrical connection           | Screw-clamp terminals, clamping capacity: 1 x 0.34...2 x 1.5 mm <sup>2</sup>   |
| Contacts insulation form        | Zb   |
| Contacts material               | Silver plated contacts   |
| Positive opening                | With   |
| Minimum actuation speed         | 0.03 ft/s (0.01 m/s)   |
| Contact code designation        | R300, DC-13 (Ue = 250 V, Ie = 0.1 A) conforming to EN/IEC 60947-5-1 appendix A<br>B300, AC-15 (Ue = 240 V, Ie = 1.5 A) conforming to EN/IEC 60947-5-1 appendix A |

|  |   |
|--|---|
| [Ui] rated insulation voltage          | 300 V conforming to CSA C22.2 No 14<br>500 V degree of pollution 3 conforming to IEC 60947-1<br>300 V conforming to UL 508  |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947-1<br>6 kV conforming to IEC 60664  |
| Short circuit protection               | 10 A by gG cartridge fuse   |
| Electrical durability                  | 5000000 cycles, DC-13 48 V, 7 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 24 V, 10 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 120 V, 4 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Width                                  | 1.22 in (31 mm)   |
| Height                                 | 2.56 in (65 mm)   |
| Depth                                  | 1.18 in (30 mm)   |
| Product weight                         | 0.31 lb(US) (0.14 kg)   |

## Environment

|                                       |                            |
|---------------------------------------|----------------------------|
| Product compatibility                 | XCKD                       |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C) |

## Ordering and shipping details

|                       |   |
|-----------------------|---|
| Category              | 22418 - LIMIT SWITCH,IEC,XCKP&XCKT                        |
| Discount Schedule     | T   |
| GTIN                  | 00785901660309  |
| Nbr. of units in pkg. | 1   |
| Package weight(Lbs)   | 0.80  |
| Product availability  | Non-Stock - Not normally stocked in distribution facility |
| Returnability         | Y   |
| Country of origin     | FR  |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS                             | Compliant - since 1002 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                     |
| Product environmental profile    | Available <a href="#">Download Product Environmental</a>                              |
| Product end of life instructions | Need no specific recycling operations   |

## Contractual warranty

|        |           |
|--------|-----------|
| Period | 18 months |
|--------|-----------|

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[ZCD29](#)