

Customer Information Sheet

DRAWING No.: M22-543XX05


IF IN DOUBT - ASK

(C)

NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm



ORDER CODE:

M22-543XX05

No. OF CONTACTS PER ROW:
03 TO 15, 20

SPECIFICATION:

MATERIAL:

MOULDING = PA9T, UL94V-0, BLACK

CONTACT = BRASS

FINISH:

CONTACT = GOLD FLASH OVER NICKEL

ELECTRICAL:

CURRENT RATING = 1.5A

CONTACT RESISTANCE = $20\text{m}\Omega$ MAX

INSULATION RESISTANCE = $1000\text{M}\Omega$ MIN

DIELECTRIC STRENGTH = 500V AC/DC MINUTE

ENVIRONMENTAL:




TEMPERATURE RANGE = -40°C TO $+105^{\circ}\text{C}$

PACKING: BOX

FOR COMPLETE SPECIFICATION, SEE COMPONENT SPECIFICATION C018XX (LATEST ISSUE)

NOTES:

1. DIMENSION TOLERANCES = ± 0.25 UNLESS OTHERWISE STATED.



RECOMMENDED PCB LAYOUT
(TOLERANCE = ± 0.05)

MSP	10	09.08.17	20547
NAME	ISS.	DATE	C/NOTE
APPROVED:		M.PERREN	
CHECKED:		S.BENNETT	
DRAWN:		J. EVANS	
CUSTOMER REF.:			
ASSEMBLY DRG:			

HARWIN

www.harwin.com
technical@harwin.com

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES

X = $\pm 1\text{mm}$
X.X = $\pm 0.50\text{mm}$
X.XX = $\pm 0.10\text{mm}$
X.XXX = $\pm 0.01\text{mm}$
ANGLES = $\pm 5^{\circ}$
UNLESS STATED

MATERIAL:

SEE ABOVE

FINISH:

SEE ABOVE

S/AREA:

mm²

TITLE:

2.00mm PITCH DIL HORIZONTAL
SMT PIN HEADER ASSEMBLY

DRAWING NUMBER:

M22-543XX05

SHT
2 OF 2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Harwin:

[M22-5430805](#) [M22-5431205](#) [M22-5432005](#) [M22-5430405](#) [M22-5431405](#) [M22-5430605](#) [M22-5431005](#) [M22-5430505](#) [M22-5431305](#) [M22-5430905](#) [M22-5430705](#) [M22-5431105](#) [M22-5430305](#) [M22-5431505](#)