

[illegible]

SECTION T-T

HOUSING

POST, TYP

6.10 TYP
[.240]

2.54
[.100]
TYP

0.64±0.03
[.025±.001]
TYP

2.72
[.107]
TYP

7.34
[.289]

2.79 ±0.25 TYP
[.110±.010]
SOLDER TAIL

0.64±0.03
[.025±.001]
TYP

SEE DETAIL V

AT POST TIPS

AT POST TIPS

Surface finish symbols: $\oplus$ 0.38 [.015] $\textcircled{M}$ Z X and $\oplus$ 0.38 [.015] $\textcircled{M}$ Z X W $\textcircled{S}$

Technical drawing of a mechanical assembly, likely a probe or test head, showing various dimensions and features.

Key features and dimensions:

- POSN NO 1 INDICATOR**: Points to a feature on the left side.
- EJECTION LATCH, TYP**: Points to a feature on the right side.
- Dimensions**:
 - 10.57 TYP [.416]
 - 0.64 ± 0.03 [.025 ± .001] TYP
 - 0.38 [.015] [M] Z X Y AT POST TIPS
 - 13.94 ± 0.20 [.549 ± .008] TYP
 - 23.09 ± 0.51 [.909 ± .020] TYP
 - 2.74 ± 0.15 [.108 ± .006] 2 PLC
 - 4.95 [.195] 2 PLC
 - Ø2.44 ± 0.08 [.096 ± .003] 2 PLC
 - 10.57 TYP [.416]
 - 0.64 ± 0.03 [.025 ± .001] TYP
 - 0.38 [.015] [M] Z X Y AT POST TIPS
 - 13.94 ± 0.20 [.549 ± .008] TYP
 - 23.09 ± 0.51 [.909 ± .020] TYP
 - 2.74 ± 0.15 [.108 ± .006] 2 PLC
 - 4.95 [.195] 2 PLC
 - Ø2.44 ± 0.08 [.096 ± .003] 2 PLC
 - 10.57 TYP [.416]
 - 0.64 ± 0.03 [.025 ± .001] TYP
 - 0.38 [.015] [M] Z X Y AT POST TIPS
 - 13.94 ± 0.20 [.549 ± .008] TYP
 - 23.09 ± 0.51 [.909 ± .020] TYP
 - 2.74 ± 0.15 [.108 ± .006] 2 PLC
 - 4.95 [.195] 2 PLC
 - Ø2.44 ± 0.08 [.096 ± .003] 2 PLC
- Coordinate System**:
 - Z**: Vertical axis (up/down).
 - S**: Horizontal axis (left/right).
 - D**: Depth axis (into/out of page).
- Other Labels**:
 - AMP
 - ®
 - LOCAL PLATE


Technical drawing of a detail of a plate area, showing dimensions and features:

- Overall length: 5.08 MIN [.200] TYP
- Length of localized plate area: 3.81 MIN [.150] TYP
- Localized plate area: LOCALIZED PLATE AREA
- Gold flash: GOLD FLASH TYP (indicated on the right side of the plate area)
- Gold flash: GOLD FLASH TYP (indicated on the bottom edge of the plate area)
- Length of gold flash area: 1.27 [.050] MAX TYP

DETAIL V
SCALE 10:1

[illegible]

SEE SHEET 2 FOR TABLE & NOTES

THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-2009		DWN 01-07-05 L VARELA - DOCKS CHK 01-07-05 S. BOLASH 01-07-05		 TE Connectivity	
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME	
		APD M. WALMSLEY PRODUCT SPEC 108-40018 APPLICATION SPEC —		HEADER ASSY, UNIVERSAL, AMP-LATCH —	
MATERIAL		FINISH		SIZE	CAGE CODE
				A1	00779
WEIGHT		—		DRAWING NO	
—		—		C=5499160	
CUSTOMER DRAWING				SCALE	1 of 2
—				4:1	REV F

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-5499160-1](#)