



Heyco® Stainless Steel Cable Ties


Ball Lock Stainless Steel Strip Cable Ties - Standard and PVC Coated

| PART SPECIFICATIONS | | | | PART NO. | | DESCRIPTION | PART DIMENSIONS | | | | | | | |
|-----------------------|-------|----------------------|-------|----------------|------------------|---------------|-----------------|---------------|---------|-----|------|-------|-----|-----|
| Min. Tensile Strength | | Max. Bundle Diameter | | Standard Steel | PVC Coated Black | | A Length | | B Width | | | | | |
| Lbs. | N | in. | mm. | | | in. | mm. | in. | mm. | | | | | |
| AISI 304 | | | | | | | | | | | | | | |
| 112 | 500 | 1.18 | 30,0 | 12801 | 12801B | NTSS-0150-46A | 5.91 | 150,0 | .18 | 4,6 | | | | |
| | | 2.05 | 52,0 | 12802 | 12802B | NTSS-0200-46A | 7.87 | 200,0 | | | | | | |
| | | 2.68 | 68,0 | 12803 | 12803B | NTSS-0250-46A | 9.84 | 250,0 | | | | | | |
| | | 3.23 | 82,0 | 12805 | 12805B | NTSS-0300-46A | 11.81 | 300,0 | | | | | | |
| | | 3.86 | 98,0 | 12806 | 12806B | NTSS-0350-46A | 13.78 | 350,0 | | | | | | |
| | | 4.33 | 110,0 | 12808 | 12808B | NTSS-0400-46A | 15.75 | 400,0 | | | | | | |
| | | 5.75 | 146,0 | 12810 | 12810B | NTSS-0500-46A | 19.69 | 500,0 | | | | | | |
| | | 7.09 | 180,0 | 12812 | 12812B | NTSS-0600-46A | 23.62 | 600,0 | | | | | | |
| | | 9.50 | 240,0 | 12814 | 12814B | NTSS-0800-46A | 31.50 | 800,0 | | | | | | |
| 250 | 1115 | 2.05 | 52,0 | 12821 | 12821B | NTSS-0200-79A | 7.87 | 200,0 | .31 | 7,9 | | | | |
| | | 2.68 | 68,0 | 12822 | 12822B | NTSS-0250-79A | 9.84 | 250,0 | | | | | | |
| | | 3.23 | 82,0 | 12824 | 12824B | NTSS-0300-79A | 11.81 | 300,0 | | | | | | |
| | | 3.86 | 98,0 | 12825 | 12825B | NTSS-0350-79A | 13.78 | 350,0 | | | | | | |
| | | 4.33 | 110,0 | 12827 | 12827B | NTSS-0400-79A | 15.75 | 400,0 | | | | | | |
| | | 5.75 | 146,0 | 12829 | 12829B | NTSS-0500-79A | 19.69 | 500,0 | | | | | | |
| | | 7.09 | 180,0 | 12831 | 12831B | NTSS-0600-79A | 23.62 | 600,0 | | | | | | |
| | | 8.27 | 210,0 | 12833 | 12833B | NTSS-0700-79A | 27.56 | 700,0 | | | | | | |
| | | 9.50 | 240,0 | 12834 | 12834B | NTSS-0800-79A | 31.50 | 800,0 | | | | | | |
| | | 12.09 | 307,0 | 12836 | 12836B | NTSS-1000-79A | 39.37 | 1000,0 | | | | | | |
| | | AISI 316 | | | | | | | | | | | | |
| | | 112 | 500 | 1.18 | 30,0 | 12851 | 12851B | NTSS-0150-46B | | | 5.91 | 150,0 | .18 | 4,6 |
| 2.05 | 52,0 | | | 12852 | 12852B | NTSS-0200-46B | 7.87 | 200,0 | | | | | | |
| 2.68 | 68,0 | | | 12853 | 12853B | NTSS-0250-46B | 9.84 | 250,0 | | | | | | |
| 3.23 | 82,0 | | | 12855 | 12855B | NTSS-0300-46B | 11.81 | 300,0 | | | | | | |
| 3.86 | 98,0 | | | 12856 | 12856B | NTSS-0350-46B | 13.78 | 350,0 | | | | | | |
| 4.33 | 110,0 | | | 12858 | 12858B | NTSS-0400-46B | 15.75 | 400,0 | | | | | | |
| 5.75 | 146,0 | | | 12860 | 12860B | NTSS-0500-46B | 19.69 | 500,0 | | | | | | |
| 7.09 | 180,0 | | | 12862 | 12862B | NTSS-0600-46B | 23.62 | 600,0 | | | | | | |
| 9.50 | 240,0 | | | 12864 | 12864B | NTSS-0800-46B | 31.50 | 800,0 | | | | | | |
| 250 | 1115 | 2.05 | 52,0 | 12871 | 12871B | NTSS-0200-79B | 7.87 | 200,0 | .31 | 7,9 | | | | |
| | | 2.68 | 68,0 | 12872 | 12872B | NTSS-0250-79B | 9.84 | 250,0 | | | | | | |
| | | 3.23 | 82,0 | 12874 | 12874B | NTSS-0300-79B | 11.81 | 300,0 | | | | | | |
| | | 3.86 | 98,0 | 12875 | 12875B | NTSS-0350-79B | 13.78 | 350,0 | | | | | | |
| | | 4.33 | 110,0 | 12877 | 12877B | NTSS-0400-79B | 15.75 | 400,0 | | | | | | |
| | | 5.75 | 146,0 | 12879 | 12879B | NTSS-0500-79B | 19.69 | 500,0 | | | | | | |
| | | 7.09 | 180,0 | 12881 | 12881B | NTSS-0600-79B | 23.62 | 600,0 | | | | | | |
| | | 8.27 | 210,0 | 12883 | 12883B | NTSS-0700-79B | 27.56 | 700,0 | | | | | | |
| | | 9.50 | 240,0 | 12884 | 12884B | NTSS-0800-79B | 31.50 | 800,0 | | | | | | |
| | | 12.09 | 307,0 | 12886 | 12886B | NTSS-1000-79B | 39.37 | 1000,0 | | | | | | |

NEW PRODUCT



- For ease of assembly, position locking head so the widest end is down.
- Part Description Key: NTSS-XXXX-YYA where XXXX = length (mm) and YYA = width (mm) with A indicating AISI 304 stainless steel and B indicating AISI 316 stainless steel.
- Stainless steel cable ties have more strength and better durability than nylon cable ties.
- Locking ball design for maximum holding strength and ease of installation.
- Coated ties offer additional protection and separation of dissimilar metals for improved corrosion resistance.
- Suitable for harsh outdoor environments; conform to standard IEC92 for Marine Electrical Appliances and the requirements of CB1113-85 “Plastic Covered Metal Cable Ties”, “Steel Sea Boats Construction Level Standard.”
- Secure bundles in moist and high temperature environments with decay, fire, corrosion, and radio resistance.
- Widely used in shipping, communication, and flight applications.
- .010" (0,25 mm) thick.
- Custom lengths available.
- 100 pack standard.



NTSS

Materials

AISI 304 or 316 stainless steel with PVC coating

Quick Specs

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Heyco:

[12827B](#) [12805](#) [12803](#) [12825](#) [12829](#) [12834](#) [12836B](#) [12806](#) [12806B](#) [12810](#) [12831](#) [12831B](#) [12833B](#) [12824](#)
[12822B](#) [12802B](#) [12833](#) [12825B](#) [12805B](#) [12803B](#) [12827](#) [12802](#) [12814](#) [12808](#) [12821B](#) [12822](#) [12810B](#) [12812](#)
[12801B](#) [12812B](#) [12836](#) [12834B](#) [12814B](#) [12824B](#) [12808B](#) [12821](#) [12829B](#) [12801](#) [12828](#) [12800B](#) [12850](#) [12878](#)
[12828B](#) [12870B](#) [12815B](#) [12865B](#) [12800](#) [12870](#) [12865](#) [12878B](#) [12820](#) [12820B](#) [12850B](#) [12815](#)