



PIN ASSIGNMENT

P1(PP)	P3	P1(SP)	P2
01+02+03	NC	1	GND
13+14+15	Yellow 1	2	2
10+11+12	Black 2	3	3
04+05+06	Black 3	4	GND
07+08+09	Red 4	5	5
		6	6
		7	GND

Electrical test:
 1. Hi-Pot test: DC300V/10ms
 2. Conduct resistance: 2Ω max.
 3. Insulator resistance: 5MΩ min.
 4. 100% open, short, miswire test

NO.	NAME.	Q'TY	SPECIFICATION
⑧	PE bag	1	Clear Print black "MADE IN CHINA"+ "1PC"
⑦	Innermold	N/A	White PE
⑥	Overmold	N/A	Black PVC 45P
⑤	P3 Conn.	1	Big 4P Female/housing PH=5.08mm White Tin plate(with 4pcs terminal)
④	P2 Conn.	1	SATA 7P/F Crimp type terminal:15u" Insulator: Black PBT
③	P1 Conn.	1	SATA 7/F+15P/F Crimp type terminal:15u" Insulator: Black PBT
②	Cable	1	UL1007 18AWG(34/0.18TC) OD: 2.0mm Jacket:black*2/Yellow/Red
①	Cable	1	UL2725(26AWG(1/0.404)*2+D(1/0.32)*2+AL)*2F OD:2.2x7.8 Jacket: Red

RoHS compliant
Unit: mm

Scale	Free					Date	Name	Customer-No.
TOLERANCE						Drawn	26.08.2014	Joanna
X.	±1					Approved	18.08.2015	Amy
X.X	±0.20							ASSMANN WSW-No. AK-SATA-SP-050
DIM	TOL	①	Update the drawing	18.08.2015	Amy			Drawing-No. ASS 7213 CA rev01
		②	Drawn	26.08.2014	Joanna			Replace
Angle	TOL	Id.	Modification	Date	Name			