

Model 72999 SMB PLUG PANEL RECEPTACLE



Model 72999 SMB PLUG PANEL RECEPTACLE

Snap-on coupling and small size for fast connect and disconnect.

Features

- DC 2 GHz bandwidth.
- Meets MIL-C-39012, IEC 60169-1Q, BS9210N0007, NFC93650, CECC 22130.
- Small size and durability for RF coaxial applications.
- Precision machined and gold-plated for low loss.

Materials

- Body is machined brass with gold plating.
- Center contacts Plug is gold plated brass and Jack is gold plated beryllium copper.
- High quality PTFE insulators.
- Crimp Ferrules are nickel plated copper.
- Silicone rubber gaskets.


Ordering Information

Model: 72999

Description: SMB PLUG PANEL RECEPTACLE

USA: Sales: 800-490-2361 Technical Support: <u>technicalsupport@pomonatest.com</u> Fax: 425-446-5844 Europe: 31-(0) 40 2675 150 International: 425-446-5500

Where to Buy: www.pomonaelectronics.com



Mounting Hole

Specifications

Impedance	50 Ω
Frequency Range	DC – 2 GHz
VSWR	1.3 max.
Working Voltage	250 Vrms max.
Dielectric withstand voltage	750 Vrms
Center / Outer contact resistance	0.006/0.002 mΩ
Number of insertions	500 cycles min.
Insulation resistance	1000 MΩ min.
Temperature Range	-65° C to 165° C, -85° F to 329° F

All dimensions are in inches. Tolerances (except noted): $.xx = \pm .02^{\circ}$ (.51 mm), $.xxx = \pm .005^{\circ}$ (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies. D2003436 REV 001

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona: 72999