

| Z | | | | | I | | | |
|---|-----|------|---|-----|---------------------------|-----------|-----|------|
| | LOC | DIST | | | REVISIONS | | | |
| | AD | 00 | P | LTR | DESCRIPTION | DATE | DWN | APVD |
| - | | | | L | REVISED PER ECO-14-000066 | 27JUN2014 | NK | MM |
| | | | | | | i | | |

1 TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD.
2 THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING.
3 POINT OF MEASUREMENT FOR PLATING THICKNESS.
4 RETENTION FEATURES ON SOLDER TAILS, LOCATED AT MANUFACTURERS OPTION.
4 FOR 2 POSITION PART ONLY, THE NOTED DIMENSION IS .184±0.16
4 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

| 3.984 3.900 39 80 | 2-104432-0 |
|--|---------------------------------------|
| | 1-104432-9 |
| OBSOLETE 2.484 2.400 24 50 | 1-104432-8 |
| 1.984 1.900 19 40 | 1-104432-7 |
| 1.684 1.600 16 34 | 1-104432-6 |
| 1.484 1.400 14 30 | 1-104432-5 |
| △ 1.384 1.300 13 28 | 1-104432-4 |
| <u> </u> | 1 - 104432 - 3 |
| <u>1.184</u> 1.100 11 24 | 1 - 104432 - 2 |
| OBSOLETE 1.084 1.000 10 22 | 1 - 104432 - 1 E |
| .984 .900 9 20 | 1-104432-0 |
| .884 .800 8 18 | 104432-9 |
| .784 .700 7 16 | 104432-8 |
| .684 .600 6 14 | 104432-7 |
| ▲ .584 .500 5 12 | 104432-6 |
| OBSOLETE .484 .400 4 10 | 104432-5 |
| .384 .300 3 8 | 104432-4 |
| .284 .200 2 6 | 104432-3 |
| .184 .100 1 4 | 104432-2 |
| .084 - 2 | 104432-1 |
| NO | ASSEMBLY |
| C B A OF POST | NUMBER |
| THIS DRAWING IS A CONTROLLED DOCUMENT. H MOLL CHK 28JUN88 CHK 28JUN88 CHK 28JUN88 CHK 28JUN88 | E Connectivity |
| | |
| INCHES OTHERWISE SPECIFIED: APVD 28JUN88 NAME HEADER ASSY MOD II | BRFAKAWAY |
| $\begin{array}{c ccccccccccccccccccccccccccccccccccc$ | · · · · · · · · · · · · · · · · · · · |
| 2 PLC ± | TENTION FEATURE |
| 4 PLC ± | RESTRICTED TO |
| MATERIAL HOUSING: FLAME RETARDANT THERMOPLASTIC COLOR-BLACK COLOR-B | — |
| POST: COPPER ALLOY NOODSO NICKEL CUSTOMER DRAWING SCALE 4:1 | SHEET 1 OF 1 REV |

С

D

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: <u>104432-1</u>