

LOC	DIST	REVISIONS 変更					
J		P	LTR	DESCRIPTION	DATE	DWN	APVD
		D		REVISED PER ECR-11-001310	21APR11	TT	TM

Part No.	Pos.	QTY'S	CONN P/N (L/P)	Tube P/N	Notes
	16	40	7-6 $\triangle 3$		
720999-5	12	50	7-2		
	24	25	5-4 $\triangle 3$		
	22	30	5-2		
	20	30	5-0 $\triangle 3$		
	18	35	4-8 $\triangle 3$		
	16	40	4-6 $\triangle 3$		
	14	45	4-4		
	12	50	4-2 $\triangle 3$		
	10	60	4-0		
720999-4	6	90	3-6 $\triangle 3$		
	20	30	2-0		
	16	40	1-6		
2-912050-0	14	45	1-174645-4		1-175635-4


  

名称 NAME	塩ビケース 型番 TUBE P/N	極数 Pos.	数量 (ヶ) QTY'S	コネクタ型番 (バラ状) CONN P/N (L/P)	塩ビケース詰 コネクタ型番 IN TUBE P/N

塩ビケース詰 1.25 F-P コネクタ (基板対基板接続用)  
 2列仕様 ポスト ヘッダー アッセンブリ  
 サーフェイスマウント タイプ 基板位置決め用ボス無  
 TUBE PACKAGING 1.25 F-P CONNECTOR (B-TO-B)  
 DOUBLE ROW POST HDR ASS'Y SMT TYPE WITHOUT BOSS

- 注記
1. 包装規格 : 107-5123-2
- NOTES
1. PACKAGING SPEC : 107-5123-2
- $\triangle 2$  OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI
- $\triangle 3$  OBSOLETE PARTS

THIS DRAWING IS UNPUBLISHED.  
 ALL RIGHTS RESERVED.  
 RELEASED FOR PUBLICATION  
 By -  
 COPYRIGHT

DIMENSIONS: 単位: 耗 mm	DWN J.TANIGAWA 28MAY88	MATERIAL 材料	FINISH 仕上
	CHK S.KIKUCHI 30MAY88	 TE Connectivity	
TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差	APVD N.ONOUE 30MAY88		
0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 4 PLC ± ANGLES ±	PRODUCT SPEC 製品規格	SIZE A4	CAGE CODE 00779
10ヶ以下: ±0.2 30ヶ以下: ±0.25 30ヶ以上100ヶ以下: ±0.3 角厚: ±0.3	APPLICATION SPEC 取付適用規格	DRAWING NO 番号 C-175635	RESTRICTED TO -
	WEIGHT	CUSTOMER DRAWING	
		SCALE 尺度	SHEET 1 OF 1 REV D

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[7-175635-2](#)