

Patch panels - VS-PP-F-SCRJ - 1658121

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Patch panel, SC-RJ, DIN rail mounting, IP20, 1 slot, socket/socket, can be used for glass, multi-mode, PCF, and polymer fibers



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	50.4 g
Custom tariff number	85366990
Country of origin	Switzerland

Technical data

Mechanical characteristics

Number of positions	2
Number of slots	1
Connection profile	SCRJ according to DIN EN 50377-6-1
Fiber type	GOF, PCF, POF
Ferrule diameter	2.50 mm
Insertion/withdrawal cycles	≥ 500
External cable diameter	4.5 mm 8 mm
Color	gray
Mounting type	DIN rail mounting

Ambient conditions

Ambient temperature (operation)	-10 °C 60 °C

Material data

Flammability rating according to UL 94	V0
Housing material	PC-GF
Ferrule material	Zirconia ceramics



Patch panels - VS-PP-F-SCRJ - 1658121

Technical data

Material data

Ferrule holder color	white
Electrical characteristics	
Number of positions	2
Standards and Regulations	
Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 4.0	272607XX
eCl@ss 4.1	27260701
eCl@ss 5.0	19030109
eCl@ss 5.1	19030109
eCl@ss 6.0	19170107
eCl@ss 7.0	19170112
eCl@ss 8.0	19170112

ETIM

ETIM 3.0	EC001128
ETIM 4.0	EC001128
ETIM 5.0	EC001128

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

EAC



Patch panels - VS-PP-F-SCRJ - 1658121

Approvals

Ex Approvals


Approvals submitted


Approval details

EAC

Drawings

Dimensional drawing





SCRJ patch panel

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1658121