

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** [1715751117](#)  
**Status:** **Active**  
**Overview:** [Impact™ Backplane Connectors and Cable Assemblies](#)  
**Description:** Impact 100 Ohm 5 Pair Right-Angle Orthogonal Direct Header, Unguided, Dual Endwall, with Outrigger, 10 Column, 90#Mate Position, Pin Length 4.90mm, Plated Through-Hole Dimension 0.39mm, Lead-Free

|                                                                   |                                                                  |
|-------------------------------------------------------------------|------------------------------------------------------------------|
| <b>Documents:</b>                                                 |                                                                  |
| <a href="#">3D Model</a>                                          | <a href="#">Application Specification AS-76850-990-001 (PDF)</a> |
| <a href="#">Drawing (PDF)</a>                                     | <a href="#">Packaging Specification PK-70873-8022-001 (PDF)</a>  |
| <a href="#">Product Specification PS-45499-002-001 (PDF)</a>      | <a href="#">Packaging Specification PK-70873-8023-001 (PDF)</a>  |
| <a href="#">Product Specification PS-76060-999-001 (PDF)</a>      | <a href="#">RoHS Certificate of Compliance (PDF)</a>             |
| <a href="#">Application Specification AS-76060-9999-001 (PDF)</a> |                                                                  |

|                                |                                                                   |
|--------------------------------|-------------------------------------------------------------------|
| <b>Agency Certification</b>    |                                                                   |
| UL                             | E29179                                                            |
| <b>General</b>                 |                                                                   |
| Product Family                 | Backplane Connectors                                              |
| Series                         | <a href="#">171575</a>                                            |
| Application                    | Orthogonal Direct                                                 |
| Application Tooling Documents  | TM-622018799                                                      |
| Component Type                 | PCB Header                                                        |
| Overview                       | <a href="#">Impact™ Backplane Connectors and Cable Assemblies</a> |
| Product Name                   | Impact                                                            |
| UPC                            | 887191301518                                                      |
| <b>Physical</b>                |                                                                   |
| Circuits (Loaded)              | 150                                                               |
| Circuits (maximum)             | 150                                                               |
| Color - Resin                  | Black                                                             |
| Durability (mating cycles max) | 200                                                               |
| First Mate / Last Break        | No                                                                |
| Flammability                   | 94V-0                                                             |
| Guide to Mating Part           | No                                                                |
| Keying to Mating Part          | None                                                              |
| Material - Metal               | High Performance Alloy (HPA)                                      |
| Material - Plating Mating      | Gold                                                              |
| Material - Plating Termination | Tin                                                               |
| Material - Resin               | High Temperature Thermoplastic                                    |
| Net Weight                     | 30.687/g                                                          |
| Number of Columns              | 10                                                                |
| Number of Pairs                | 5                                                                 |
| Number of Rows                 | 15                                                                |
| Orientation                    | Right Angle                                                       |
| PC Tail Length                 | 1.20mm                                                            |
| PCB Locator                    | No                                                                |
| PCB Retention                  | Yes                                                               |
| PCB Thickness - Recommended    | 1.00mm                                                            |
| Packaging Type                 | Tray                                                              |
| Pitch - Mating Interface       | 1.35mm, 1.90mm, 2.15mm                                            |
| Pitch - Termination Interface  | 1.35mm, 1.90mm, 2.15mm                                            |
| Plating min - Mating           | 0.762µm                                                           |
| Polarized to PCB               | Yes                                                               |
| Stackable                      | No                                                                |
| Surface Mount Compatible (SMC) | No                                                                |
| Temperature Range - Operating  | -55° to +85°C                                                     |



Series image - Reference only

|                                                               |                   |
|---------------------------------------------------------------|-------------------|
| <b>EU ELV</b>                                                 |                   |
| <b>Not Relevant</b>                                           |                   |
| <b>EU RoHS</b>                                                | <b>China RoHS</b> |
| <b>Compliant</b>                                              |                   |
| <b>REACH SVHC</b>                                             |                   |
| Not Contained Per - ED/71/2019 (16 July 2019)                 |                   |
| <b>Halogen-Free Status</b>                                    |                   |
| <b>Not Low-Halogen</b>                                        |                   |
| For more information, please visit <a href="#">Contact US</a> |                   |
| China ROHS                                                    | Green Image       |
| ELV                                                           | Not Relevant      |
| RoHS Phthalates                                               | Not Contained     |

**Search Parts in this Series**  
[171575 Series](#)

**Mates With**  
[76990](#) Impact 100 Ohm Right Angle Orthogonal Daughtercard

| <b>Application Tooling   FAQ</b>                                                                                                                                                       |                           |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|
| <i>Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.</i> |                           |
| <b>Global</b>                                                                                                                                                                          |                           |
| Description                                                                                                                                                                            | Product #                 |
| Impact Daughter Card Extraction Tool                                                                                                                                                   | <a href="#">622024300</a> |
| Impact Orthogonal Direct Ram Module Installation Press-In Tool 5-Pair by 10 Column                                                                                                     | <a href="#">622030028</a> |

|                                    |                                      |
|------------------------------------|--------------------------------------|
| Termination Interface: Style       | Through Hole - Compliant Pin         |
| <b>Electrical</b>                  |                                      |
| Current - Maximum per Contact      | 0.75A                                |
| Data Rate                          | 25.0 Gbps                            |
| Impedance                          | 100Ω                                 |
| Shield Type                        | N/A                                  |
| Shielded                           | No                                   |
| Voltage - Maximum                  | 30V AC (RMS)/DC                      |
| <b>Solder Process Data</b>         |                                      |
| Lead-freeProcess Capability        | N/A                                  |
| <b>Material Info</b>               |                                      |
| <b>Reference - Drawing Numbers</b> |                                      |
| Application Specification          | AS-76060-9999-001, AS-76850-990-001  |
| Packaging Specification            | PK-70873-8022-001, PK-70873-8023-001 |
| Product Specification              | PS-45499-002-001, PS-76060-999-001   |
| Sales Drawing                      | SD-171575-0001                       |
| Symbol/Footprint Data              | SYM-171575-1117                      |

This document was generated on 09/21/2019

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex:

171575-1117