

SPDT High Isolation Terminated Switch 0.01 - 3.0 GHz

Rev. V4

Features

- Positive Voltage Control: 0 / +5 V
- High Isolation: 55 dB @ 0.9 GHz
50 dB @ 1.9 GHz
- 50 Ω Internal Terminations
- Low Insertion Loss: 0.6 dB @ 0.9 GHz
0.7 dB @ 1.9 GHz
- Lead-Free MSOP-8-EP Package
- Halogen-Free "Green" Mold Compound
- 260°C Reflow Compatible
- RoHS* Compliant Version of MASWSS0024

Description

The MASWSS0178 GaAs monolithic switch provides high isolation in a lead-free, plastic surface mount package.

The MASWSS0178 is ideal for applications across a broad range of frequencies including synthesizer switching, transmit / receive switching, switch matrices and filter banks in systems such as radio and cellular equipment, PCS, GPS, and fiber optic modules.


M/A-COM Technology fabricates the MASWSS0178 using a 1.0-micron gate length MESFET process. The process features full chip passivation for performance and reliability.

Ordering Information ¹

| Part Number | Package |
|-------------------|-----------------|
| MASWSS0178 | Bulk Packaging |
| MASWSS0178TR-3000 | 3000 piece reel |
| MASWSS0178SMB | Sample Board |

1. Reference Application Note M513 for reel size information.

Functional Schematic ²



2. The exposed pad centered on the package bottom must be connected to RF and DC ground.

Pin Configuration

| Pin No. | Function | Pin No. | Function |
|---------|-----------|---------|-----------|
| 1 | Control 1 | 5 | RF Port 2 |
| 2 | Control 2 | 6 | Ground |
| 3 | RF Common | 7 | Ground |
| 4 | Ground | 8 | RF Port 1 |

Absolute Maximum Ratings ^{3,4}

| Parameter | Absolute Maximum |
|---|--------------------|
| Input Power (0.5 - 3.0 GHz) 3 V Control 5 V Control | +30 dBm +33 dBm |
| Operating Voltage | +8.5 Volts |
| Operating Temperature | -40°C to +85°C |
| Storage Temperature | -65°C to +150°C |

3. Exceeding any one or combination of these limits may cause permanent damage to this device.
4. M/A-COM Technology does not recommend sustained operation near these survivability limits.

* Restrictions on Hazardous Substances, European Union Directive 2002/95/EC.

SPDT High Isolation Terminated Switch 0.01 - 3.0 GHz

Rev. V4

Electrical Specifications: $T_A = 25^\circ\text{C}$, $V_C = 0\text{ V} / 5\text{ V}$, $Z_0 = 50\ \Omega$ ⁵

| Parameter | Test Conditions | Units | Min. | Typ. | Max. |
|------------------------|---|---------------|------|------|------|
| Insertion Loss | 0.01 - 0.5 GHz | dB | — | 0.5 | — |
| | 0.5 - 1.0 GHz | | — | 0.6 | 0.7 |
| | 1.0 - 2.0 GHz | | — | 0.7 | 0.8 |
| | 2.0 - 3.0 GHz | | — | 0.75 | — |
| Isolation | 0.01 - 0.5 GHz | dB | — | 59 | — |
| | 0.5 - 1.0 GHz | | 51 | 57 | — |
| | 1.0 - 2.0 GHz | | 44 | 53 | — |
| | 2.0 - 3.0 GHz | | — | 43 | — |
| Return Loss | 0.01 - 0.5 GHz ⁶ | dB | — | 20 | — |
| | 0.5 - 1.0 GHz | | — | 20 | — |
| | 1.0 - 2.0 GHz | | — | 20 | — |
| | 2.0 - 3.0 GHz | | — | 20 | — |
| Input IP ₂ | 2-Tone, 900 MHz, 5 MHz spacing | dBm | — | 83 | — |
| Input IP ₃ | 2-Tone, 900 MHz, 5 MHz spacing | dBm | — | 43 | — |
| Input P1dB Compression | $V_C = 0\text{ V}/5.0\text{ V}$, 1 GHz | dBm | — | 29 | — |
| | $V_C = 0\text{ V}/3.0\text{ V}$, 1 GHz | | — | 17.5 | — |
| Trise, Tfall | 10% to 90% RF & 90% to 10% RF | ns | — | 24 | — |
| Ton, Toff | 50% of V_C to 10% / 90% RF | ns | — | 15 | — |
| Transients | In-band | mV | — | 12 | — |
| Control Current | $V_C = 5\text{ V}$ | μA | — | 2 | 13 |

5. External DC blocking capacitors are required on all RF ports (47 pF capacitors are recommended). Use larger value capacitors for lower frequency operation (e.g. use 10,000 pF capacitors to optimize insertion and return loss at frequencies below 50 MHz).

6. Terminated return loss is governed by blocking capacitors internal to the device; see applications plot.

Truth Table

| V1 | V2 | RFC-RF1 | RFC-RF2 |
|----|----|---------|---------|
| 0 | 1 | Off | On |
| 1 | 0 | On | Off |

| Logic Level | Voltage Level |
|-----------------------|----------------------|
| V_{LOW} "0" | $0 \pm 0.2\text{ V}$ |
| V_{HIGH} "1" | 3.0 V to 8.0 V |

Handling Procedures

Please observe the following precautions to avoid damage:

Static Sensitivity


Gallium Arsenide Integrated Circuits are sensitive to electrostatic discharge (ESD) and can be damaged by static electricity. Proper ESD control techniques should be used when handling these devices.

SPDT High Isolation Terminated Switch 0.01 - 3.0 GHz


Rev. V4

Typical Performance Curves


Return Loss




Insertion Loss



Isolation



Lead-Free MSOP-8-EP†




† Reference Application Note M538 for lead-free solder reflow recommendations

Meets JEDEC moisture sensitivity level 1 requirements.
Plating is 100% matte tin over copper.


Applications Section

Typical Performance Curves, Very Low Frequency, 10000 pF Blocking Capacitors


Return Loss vs. Frequency



Insertion Loss vs. Frequency



Isolation vs. Frequency



M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.