

LOC		DIST		REVISIONS					
—		—		P	LTR	DESCRIPTION	DATE	DWN	APVD
NUMMER 829309				E		Contact pin base material change from CuSn (Phosphor bronze) to CuZn (Brass). Plating change from MIN. 0.8µm gold plating to min. 0.7µm Pd Ni + 0.1µm gold flash at contact area (Area F).	22JUL2014	TJ	JK
VERWENDET FÜR									
WAR NR. E88-52544									

POLZ. PRO REIHE	L±0.4	BESTELL-NR.
—	—	—
2	5.08	— 2 [△]
3	7.62	— 3
4	10.16	— 4
5	12.70	— 829 309 5 [△]
6	15.24	— 6
7	17.78	— 7 [△]
8	20.32	— 8
9	22.86	— 9
10	25.40	1 — 0 [△]
11	27.94	1 — 1 [△]
12	30.48	1 — 2 [△]
13	33.02	1 — 3 [△]
14	35.56	1 — 4 [△]
15	38.10	1 — 5
16	40.64	1 — 6 [△]
17	43.18	1 — 7
18	45.72	1 — 8
19	48.26	1 — 9
20	50.80	2 — 0
21	53.34	2 — 1
22	55.88	2 — 2
23	58.42	2 — 3
24	60.96	2 — 4
25	63.50	2 — 5 [△]
26	66.04	2 — 6
27	68.58	2 — 7
28	71.12	2 — 8 [△]
29	73.66	2 — 9
30	76.20	3 — 0
31	78.74	3 — 1
32	81.28	3 — 2 [△]
33	83.82	3 — 3
34	86.36	3 — 4 [△]
35	88.90	3 — 5
36	91.44	3 — 6
37	93.98	3 — 7
38	96.52	3 — 8
39	99.06	3 — 9
40	101.60	4 — 0
41	104.14	4 — 1
42	106.68	4 — 2
43	109.22	4 — 3
44	111.76	4 — 4
45	114.30	4 — 5
46	116.84	4 — 6
47	119.38	4 — 7
48	121.92	4 — 8
49	124.46	4 — 9
50	127.00	5 — 829 309 0 [△]

RELEASED FOR PUBLICATION


ALL RIGHTS RESERVED.

By -

COPYRIGHT -

©

THIS DRAWING IS UNPUBLISHED.

0 PLC
1 PLC
2 PLC
3 PLC
4 PLC
ANGLESDIMENSIONS:
mmTOLERANCES UNLESS
OTHERWISE SPECIFIED:±0.2 mm
± -
± -
± -
± -
± -

DWN

G.Holaus

17.07.89

CHK

M.Schaarschmidt

APVD

PRODUCT SPEC

108-18012

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

MATERIAL

SEE TABLE

FINISH

SEE TABLE



TE Connectivity

NAME

SPEZ. AMPMODU II STIFTELEISTE
ZWEIREIHIG

SIZE

A4

CAGE CODE

00779

DRAWING NO

C-829309

RESTRICTED TO

—

SCALE

4:1

SHEET

1 OF 1

REV

E

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-829309-0](#)