


LOC J	DIST /	REVISIONS 変更			DATE	DWN	APVD
P	LTR	DESCRIPTION					
	H3	REVISED PER ECO-13-012188			05AGU13	B.P	D.Z



1 APPLICABLE CONTACT P/N: 175057-1

△ OBSOLETE PARTS: OBSOLETE CIS STERAMLINING PER D.RENAUD/D.SINSI

1 適用端子型番: 175057-1

GWT,94V-0	自然色 (NATURAL)	7-176497-1
94V-0	黒 (BLACK)	1-176497-9
94V-0	赤 (RED)	1-176497-7
94V-0	青 (BLUE)	1-176497-6
94V-0	黄 (YELLOW)	1-176497-4
94V-0	自然色 (NATURAL)	1-176497-1
94V-2	黒 (BLACK)	176497-9
94V-2	自然色 (NATURAL)	176497-1
UL GRADE	色 (COLOR)	型番 (P/N)

GENERAL TOLERANCE
一般公差

10 ≥ : ±0.2
30 ≥ > 10: ±0.25
100 ≥ > 30: ±0.3
ANGLES: ±3°

WIRE RANGE 抱合電線断面積	INSULATION DIA 被覆外径	2.8~4.2 mmφ
-----------------------	------------------------	-------------

THIS DRAWING IS UNPUBLISHED. ALL RIGHTS RESERVED. RELEASED FOR PUBLICATION.

DIMENSIONS:
単位: 耗
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:
一般公差

0 PLC	± -
1 PLC	± -
2 PLC	± -
3 PLC	± -
4 PLC	± -
ANGLES	± -

DWN	Y.FUJITA	10NOV1989
CHK	Y.FUJITA	10NOV1989
APVD	N.ONOUE	11NOV1989
PRODUCT SPEC	製品規格	
APPLICATION SPEC	取付適用規格	
WEIGHT		

MATERIAL 材料		6/6ナイロン (表参照) 6/6 NYLON(SEE TABLE)		FINISH 仕上
		TE Connectivity		
		ワンタッチスリーブ (250シリーズ旗型ポジティブロッカー-EX用) ONE TOUCH SLEEVE 250 SERIES FLAG POSITIVE LOCK-EX		
SIZE	CAGE CODE	DRAWING NO 番号	RESTRICTED TO	
A4	00779	C-176497		
CUSTOMER DRAWING		SCALE 尺度	NTS	SHEET 1 OF 1
		REV	H3	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-176497-1](#)