



**Product:** [3082A](#) 

DeviceBus®, 2 Pr #15+18 Str TC, PVC+PO Ins, IS+OA TC Brd, PVC Jkt, CMG PLTC

 [Request Sample](#)

## Product Description

DeviceBus® for ODVA DeviceNet™, 2 Pair 15+18AWG (19x28+19x30) Tinned Copper, PVC+PO Insulation, Individual Beldfoil® & OA Tinned Copper Braid(65%) Shield, PVC Outer Jacket, CMG PLTC

## Technical Specifications

### Product Overview

Suitable Applications:	harsh environment, ODVA device-level communication, used with CIP (common Industrial Protocol) for control, configuration, and data collection between devices, such as sensors and actuators, and higher level devices such as PLC, and PC in industrial automation, bus topology, etc.
------------------------	--

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Pairs
15	19x27	TC - Tinned Copper	1
18	19x30	TC - Tinned Copper	1

Conductor Count:	4
------------------	---

#### Insulation

Element	Material	Nominal Wall Thickness
15	PVC - Polyvinyl Chloride	0.021 in
18	PE - Polyethylene (Foam)	0.053 in

#### Color Chart

Number	Color
1 (15 AWG)	Red & Black
2 (18 AWG)	Blue & White

#### Inner Shield Material

Type	Material	Coverage [%]
Tape	Alum / Poly	100 %

#### Outer Shield Material

Type	Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Braid	TC - Tinned Copper	65 %	TC - Tinned Copper	18	19x30

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.48 in	0.06 in

### Electrical Characteristics

#### Conductor DCR

Element	Nominal Conductor DCR	Nominal Outer Shield DCR
15 AWG	3.6 Ohm/1000ft	1.8 Ohm/1000ft
18 AWG	6.9 Ohm/1000ft	

Capacitance

Element	Nom. Capacitance Conductor to Conductor
18 AWG Pair Only	
	12 pF/ft

Inductance

Element	Nominal Inductance
15 AWG Pair Only	0.174 µH/ft

Impedance

Nominal Characteristic Impedance
120 Ohm

Delay

Max. Delay	Max. Delay Description	Nominal Delay	Nominal Velocity of Propagation (VP) [%]	Nominal Velocity of Propagation (VP) Description
1.36 ns/ft	18 AWG Pair Only			18 AWG Pair Only
		1.36 ns/ft	75 %	

High Freq

Element	Frequency [MHz]	Max. Insertion Loss (Attenuation)	Max./Min. Input Impedance (unFitted)
18 AWG Pair Only	0.125 MHz	0.13 dB/100ft	120 Ohm
	0.5 MHz	0.25 dB/100ft	
	1 MHz	0.36 dB/100ft	

Current

Element	Max. Recommended Current [A]
15 AWG	8.0 Amps
18 AWG	5.0 Amps

Voltage

UL Voltage Rating
300 V RMS (PLTC, CMG)
600 V RMS (UL AWM Style 20201)
300 V RMS (C(UL) AWM)

Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

Mechanical Characteristics

Oil Resistance:	Yes
Bulk Cable Weight:	108 lbs/1000ft
Max Recommended Pulling Tension:	190 lbs
Min Bend Radius/Minor Axis:	4.8 in

Standards

NEC Articles:	800
NEC/(UL) Specification:	CMG, PLTC-ER
CEC/C(UL) Specification:	CMG
UL AWM Style:	20201
CSA AWM Specification:	AWM I/II A
CPR Euroclass:	Eca
Other Specification:	ODVA Class 2 Thick

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes

EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

### Suitability

Suitability - Oil Resistance:	Yes
Suitability - Sunlight Resistance:	Yes

### Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 FT4 Loading
CSA Flammability:	FT4
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

### Part Number

#### Variants

Item #	Color	Putup Type	Length	UPC
3082A T5U500	Gray T5U	Reel	500 ft	612825140788
3082A T5U2000	Gray T5U	Reel	2,000 ft	612825140764
3082A T5U3000	Gray T5U	Reel	3,000 ft	612825140771

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

### Product Notes

Notes:	Thick. Meter marks on jacket to aid users in installation. ODVA DeviceNet is an Open DeviceNet Vendor Associatio, Inc. Trademark. Jacket printed ""1PR16"" instead of ""1PR15"" due to UL requirements for CMG Listing.
--------	---

### History

Update and Revision:	Revision Number: 0.348 Revision Date: 04-28-2020
----------------------	--

© 2020 Belden, Inc  
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Belden Wire & Cable:](#)

[3082A T5U500](#) [3082A T5U2000](#)